ED **A19 OMNI**

9 Watt 4000K - Commercial Pack A19 OMNI LED





2.36 in

2.36 i	n			
Electrical	-			
Watt	9			
Input Current	104 (mA)			
Power Factor	> 0.90			
Voltage	120 volt			
Frequency	60hz			
Min. Start Temp	-4F			
Max. Operating Temp	104F			
Base Type	E26 Medium			
Light				
Initial Lumens	810			
Lumens per Watt	90			
Color Temperature	4000K			
Color Rendering (CRI)	81			
Beam Angle	Omni-Directional			
Agency Approvals	1			
UL	Yes			
Energy Star	25,000 rated hours			
RoHS	Yes			
FCC	Yes			
Product Details				
Warranty	10 years, 6 hrs/day			
Mercury Content	0			
Diameter	2.3622"			
Overall Length	4.6457"			

PRODUCT DESCRIPTION

9 watt A19 Omni-directional EarthBulb LED provides 810 lumens and replaces 60 watt incandescent bulbs for over 75% energy savings. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. Energy Star rated product. May be used in fully enclosed fixtures.

PRODUCT FEATURES

- This A bulb is Energy Star and provides 810 lumens, capable of dimming to less than 5%
- ≥300° beam angle provides full radial illumination
- Chipset provides 4000K cool white light with a high color rendering rating of over 81
- New heat sync system provides improved aesthetics and performance

PRODUCT APPLICATIONS



LUMINOUS DISTRIBUTION INTENSITY DATA

Y(deg)					
C(deg)	0	23	45	68	90
0	82.9	82.8	82.7	82.6	82.5
5	82.9	82.7	82.6	82.4	82.3
10	82.8	82.7	82.6	82.5	82.5
15	82.9	82.8	82.8	82.8	82.8
20	83.1	83.0	82.9	82.9	83.0
25	83.3	83.2	83.1	83.1	83.2
30	83.7	83.5	83.4	83.4	83.5
35	84.1	83.8	83.6	83.6	83.7
40	84.3	84.0	83.7	83.7	83.8
45	84.4	84.0	83.7	83.7	83.8
50	84.4	83.9	83.5	83.4	83.6
55	84.1	83.6	83.1	83.0	83.2
60	83.6	83.0	82.5	82.3	82.5
65	82.9	82.2	81.6	81.4	81.7
70	82.0	81.3	80.6	80.3	80.6
75	80.9	0.08	79.3	79.0	79.3
80	79.5	78.6	77.8	77.5	77.7
85	77.8	76.9	76.1	75.7	76.0
90	75.9	75.0	74.1	73.7	74.0

MODEL NUMBER	R: LA1994	40E		f					
Order Code	Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty			
10196	1	840791101964	00840791101964	12	84079110196400	48			
Dimensions (inches - Length x Width x Height)									
10196	1	2.56 x 2.56 x 5.11	10.78 x 8.15 x 5.78	12	22.36 x 17.08 x 7.13	48			
Weight (lbs)									
10196	1	0.4136	3.92	12	16.53	48			


EarthTronics 380 W. Western Ave, Suite 301 Muskegon, Michigan 49440 PH 231.332.1188 Toll Free 866.632.7840 Fax 231.726.5029 www.earthtronics.com





Master Pack

LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):289.6°

Note: IES files available upon request.

Inner Pack



Individual