A19 OMNI

9 Watt 2700K, 48 pc Bulk Pack A19 OMNI LED





| 2.30 111 | | | | | |
|--------------------------|---------------------|--|--|--|--|
| Electrical | | | | | |
| Watt | 9 | | | | |
| Input Current | 104 (mA) | | | | |
| Power Factor | > 0.90 | | | | |
| Voltage | 120 volt | | | | |
| Frequency | 60hz | | | | |
| Min. Start Temp | -4F | | | | |
| Max. Operating Temp | 104F | | | | |
| Base Type | E26 Medium | | | | |
| Light | | | | | |
| Initial Lumens | 810 | | | | |
| Lumens per Watt | 90 | | | | |
| Color Temperature | 2700K | | | | |
| Color Rendering (CRI) | 81 | | | | |
| Beam Angle | 300° | | | | |
| Agency Approvals | | | | | |
| UL | Yes | | | | |
| Energy Star | 25,000 rated hours | | | | |
| RoHS | Yes | | | | |
| FCC | Yes | | | | |
| Product Details | | | | | |
| Warranty | 10 years, 6 hrs/day | | | | |
| Mercury Content | 0 | | | | |
| Diameter | 2.3622" | | | | |
| Overall Length | 4.6457" | | | | |

PRODUCT DESCRIPTION

9 watt A19 Omni-directional EarthBulb LED provides 810 lumens and replaces 60 watt incandescent directional bulbs for over 75% energy savings. 2700K color of light is standard. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. Energy Star rated product. Sold in 48 bulk case. May be used in fully enclosed fixtures.

PRODUCT FEATURES

- This A bulb is Energy Star and provides 810 lumens, capable of dimming to less than 5%
- ≥300° beam angle provides full radial illumination
- Chipset provides 2700K soft light with a high color rendering rating of over 81
- New heat sync system provides improved aesthetics and performance

PRODUCT APPLICATIONS










LUMINOUS DISTRIBUTION INTENSITY DATA

| Y(deg) | | | | | |
|--------|------|------|------|------|------|
| C(deg) | 0 | 23 | 45 | 68 | 90 |
| 0 | 82.9 | 82.8 | 82.7 | 82.6 | 82.5 |
| 5 | 82.9 | 82.7 | 82.6 | 82.4 | 82.3 |
| 10 | 82.8 | 82.7 | 82.6 | 82.5 | 82.5 |
| 15 | 82.9 | 82.8 | 82.8 | 82.8 | 82.8 |
| 20 | 83.1 | 83.0 | 82.9 | 82.9 | 83.0 |
| 25 | 83.3 | 83.2 | 83.1 | 83.1 | 83.2 |
| 30 | 83.7 | 83.5 | 83.4 | 83.4 | 83.5 |
| 35 | 84.1 | 83.8 | 83.6 | 83.6 | 83.7 |
| 40 | 84.3 | 84.0 | 83.7 | 83.7 | 83.8 |
| 45 | 84.4 | 84.0 | 83.7 | 83.7 | 83.8 |
| 50 | 84.4 | 83.9 | 83.5 | 83.4 | 83.6 |
| 55 | 84.1 | 83.6 | 83.1 | 83.0 | 83.2 |
| 60 | 83.6 | 83.0 | 82.5 | 82.3 | 82.5 |
| 65 | 82.9 | 82.2 | 81.6 | 81.4 | 81.7 |
| 70 | 82.0 | 81.3 | 80.6 | 80.3 | 80.6 |
| 75 | 80.9 | 80.0 | 79.3 | 79.0 | 79.3 |
| 80 | 79.5 | 78.6 | 77.8 | 77.5 | 77.7 |
| 85 | 77.8 | 76.9 | 76.1 | 75.7 | 76.0 |
| 90 | 75.9 | 75.0 | 74.1 | 73.7 | 74.0 |

LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):289.6°

Note: IES files available upon request.

MODEL NUMBER: LA19927E ORDER CODE: 10217









