LED A19 OMNI

9 Watt 3000K - Commercial Pack A19 OMNI LED





Electrical						
Watt	9					
Input Current	104 (mA)					
Power Factor	> 0.50					
Voltage	120 volt					
Frequency	60hz					
Min. Start Temp	-4F					
Max. Operating Temp	104F					
Base Type	E26 Medium					
Light						
Initial Lumens	810					
Lumens per Watt	90					
Color Temperature	3000K					
Color Rendering (CRI)	81					
Beam Angle	Omni-Directional					
Agency Approvals						
UL	Yes					
Energy Star	25,000 rated hours					
RoHS	Yes					
FCC	Yes					
Product Details						
Warranty	10 years, 6 hrs/day					
Mercury Content	0					
Diameter	2.3622"					
Overall Length	4.6457"					

PRODUCT DESCRIPTION

9 watt A19 Omni-directional EarthBulb LED provides 810 lumens and replaces 60 watt incandescent bulbs for over 75% energy savings. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. May be used in fully enclosed fixtures. Suitable for outdoor use, damp location, when installed in fixtures and not directly exposed to weather. Energy Star rated product.

PRODUCT FEATURES

- This A bulb is Energy Star and provides 810 lumens, capable of dimming to less than 5%
- ≥300° beam angle provides full radial illumination
- Chipset provides 3000K white light with a high color rendering rating of over 81
- New heat sync system provides improved aesthetics and performance

PRODUCT APPLICATIONS












LUMINOUS DISTRIBUTION INTENSITY DATA

Y(deg)					
C(deg)	0	23	45	68	90
0	82.9	82.8	82.7	82.6	82.5
5	82.9	82.7	82.6	82.4	82.3
10	82.8	82.7	82.6	82.5	82.5
15	82.9	82.8	82.8	82.8	82.8
20	83.1	83.0	82.9	82.9	83.0
25	83.3	83.2	83.1	83.1	83.2
30	83.7	83.5	83.4	83.4	83.5
35	84.1	83.8	83.6	83.6	83.7
40	84.3	84.0	83.7	83.7	83.8
45	84.4	84.0	83.7	83.7	83.8
50	84.4	83.9	83.5	83.4	83.6
55	84.1	83.6	83.1	83.0	83.2
60	83.6	83.0	82.5	82.3	82.5
65	82.9	82.2	81.6	81.4	81.7
70	82.0	81.3	80.6	80.3	80.6
75	80.9	80.0	79.3	79.0	79.3
80	79.5	78.6	77.8	77.5	77.7
85	77.8	76.9	76.1	75.7	76.0
90	75.9	75.0	74.1	73.7	74.0

LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):289.6°

Note: IES files available upon request.







MODEL NUMBER: LA19930D6

Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty				
1	84079110255x	0084079110255x	12	84079110255x00	48				
Dimensions (inches - Length x Width x Height)									
1	2.56 x 2.56 x 5.11	10.78 x 8.15 x 5.78	12	22.36 x 17.08 x 7.13	48				
Weight (lbs)									
1	0.4136	3.92	12	16.53	48				
	1	1 84079110255x ength x Width x Height) 1 2.56 x 2.56 x 5.11	1 84079110255x 0084079110255x ength x Width x Height) 1 2.56 x 2.56 x 5.11 10.78 x 8.15 x 5.78	1 84079110255x 0084079110255x 12 ength x Width x Height) 1 2.56 x 2.56 x 5.11 10.78 x 8.15 x 5.78 12	1 84079110255x 0084079110255x 12 84079110255x00 ength x Width x Height) 1 2.56 x 2.56 x 5.11 10.78 x 8.15 x 5.78 12 22.36 x 17.08 x 7.13				





