LED PAR16

6 Watt 3000K PAR16 LED





Electrical					
Watt	6.5				
Input Current	143 (mA)				
Power Factor	> 0.80				
Voltage	120 volt				
Frequency	60hz				
Min. Start Temp	-4F				
Max. Operating Temp	104F				
Base Type	E26 Medium				
Light					
Initial Lumens	500				
Lumens per Watt	76				
Color Temperature	3000K				
Color Rendering (CRI)	84				
Beam Angle	38°				
Agency Approvals					
UL	Yes				
Energy Star	Yes, 25,000 Hours				
RoHS	Yes				
FCC	Yes				
Product Details					
Warranty	10 years, 6 hrs/day				
Mercury Content	0				
Diameter	1.92"				
Overall Length	2.88"				

PRODUCT DESCRIPTION

6.5 watt PAR16 EarthBulb LED bulb replaces 50 watt incandescent floodlights for over 80% energy savings. 3000K white light provides great than 83 CRI. Great for use in dimming recessed lighting, track lighting and display lighting applications. Multi-Chipset high power LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base.

PRODUCT FEATURES

- Dimming PAR16 flood light is provides 500 lumens, capable of dimming to less than 5%
- 38° beam angle provides a floodlight illumination
- Chipset provides 3000K white white with a high color rendering rating of 83

PRODUCT APPLICATIONS









MODEL NUMBER: LP16630D6

Order Code	Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty	
10400	1	840791104002	00840791104002	12	84079110400200	48	
Dimensions (inches - Length x Width x Height)							
10400	1	2.05 x 2.05 x 2.99	8.75 x 6.62 x 3.67	12	13.63 x 9.10 x 7.96	48	
Weight (lbs)							
10400	1	0.15	2.43	12	10.10	48	



