# PAR30

## 800 Lumen 13 Watt 3000K PAR30 - 40° Commercial Pack






Electrical				
Watt	13			
Power Factor	> 0.9			
Voltage	120 volt			
Frequency	60Hz			
Base Type	E26 Medium			
Operating Temperature Range	-4F to 104F			
Light				
Initial Lumens	800			
Lumens per Watt	62			
Color Temperature	3000K			
Color Rendering (CRI)	93			
Beam Angle	40°			
Agency Approvals				
UL	Yes			
Energy Star	25,000 hours			
RoHS	Yes			
FCC	Yes			
Product Details				
Warranty	10 years 6 hr/day			
Diameter	3.63"			
Nominal Length	4.59"			

#### PRODUCT DESCRIPTION

13 watt PAR30 EarthBulb LED floodlight replaces 75 watt incandescent floodlights for over 85% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. Suitable for outdoor use, damp location rated.

#### PRODUCT FEATURES

- Dimming PAR30 flood light provides 800 lumens, capable of dimming to less
- 40° beam angle provides a flood, not spot light
- Unique LED array design look like halogen when powered on
- Chipset provides 3000K white light with a high color rendering rating over 80, 90+ CRI
- Wet rated UL and suitable for exterior locations
- Face of the lamp looks like standard PAR lamps
- Fits track heads like a PAR lamp is intended



#### PRODUCT APPLICATIONS






#### **LUMINOUS DISTRIBUTION INTENSITY DATA**

ensity (	_				
H(°)	0	22.5	45	67.5	90
0	1947	1947	1947	1947	1947
5	1904	1887	1875	1863	1852
10	1712	1683	1655	1632	1604
15	1354	1310	1279	1251	1209
20	903.8	858.4	840.9	820.3	779.2
25	515.6	484.1	477.4	466.8	440.8
30	265.4	249.6	250.3	248.9	241.3
35	137.8	131.7	133.2	135.4	131.2
40	79.9	76.9	77.8	79.8	78.2
45	53.0	51.6	52.2	52.9	52.1
50	39.2	38.5	38.8	38.7	38.0
55	30.7	30.1	30.2	30.0	29.4
60	24.4	23.9	23.9	23.5	23.2
65	19.2	18.7	18.6	18.2	17.8
70	14.5	14.1	14.1	13.6	13.2
75	10.6	10.2	10.1	9.7	9.4
80	7.2	6.9	6.7	6.5	6.2
85	4.7	4.4	4.3	4.1	3.8
90	2.7	2.5	2.3	2.2	2.0

### **LUMINOUS DISTRIBUTION INTENSITY DIAGRAM**



MODEL NUMBER: LP31330D6 OPDED CODE: 10/35

ORDER CODE. 10433							
Order Code	Individual UPC	Master Park UPC	Qty				
10435	840791104354	84079110435400	12				
Dimensions (inches - Length x Width x Height)							
10435	3.93 x 3.93 x 5.08	16.61 x 12.55 x 6.14	12				
Weight (lbs)							
10/35	110	6 622	12				











