LED Panel

LED 9 inch Architectural Panel Light 19 Watt 1200 Lumens 3000K



Electrical	
Watt	19
Voltage	120
Frequency	60Hz
Power Factor	0.9
Min. Start Temperature	-40°C
Max. Operating Temperature	40°C
Light	
Initial Lumens	1200
Lumens per Watt	64
Color Temperature	3000K
Color Rendering (CRI)	90
Beam Angle	100°
Agency Approvals	
Energy Star	Yes
FCC	Yes
ETL	Yes
Product Details	
Lens Material	Acrylic
Warranty	5 years (based on 6 hours/ day)
Rated Life	50,000 hours

Product Description

The 9” LED Panel light is constructed using attractive impact resistant acrylic lens that helps achieve a wide light distribution pattern. These Panel lights are ideal for use in residential, offices, schools, healthcare, and many other commercial applications. Designed for easy installation in retrofit or new construction projects.

This 19 watt panel light produces 1200 lumens of 3000K high >90 CRI light quality. Operates on 120VAC 60Hz and is compatible with standard incandescent dimmer controls providing a 100% to 5% dimming range. Easily installs on 4” j-boxes. Also can be used as a retrofit for 4” downlight recessed fixtures with an available accessory kit.

Product Features

- Easily installs on 4” j-box
- 1200 lumens, 3000K
- Exceptional color rendering CRI >90
- Smooth edgelit LED technology
- Wet location, perfect for shower applications
- 4" recessed can accessory kit available
- Wet location rated
- 50,000 hour rated life



Order Code: MP021200309WH2

Model Number: MP021200309

UPC: 840791106426

Dia x MOL: 9.06” x 1.65”

Weight: 1.62 lb

EarthTronics 380 W. Western Ave, Suite 301 Muskegon, Michigan 49440
PH 231.332.1188 **Toll Free** 866.632.7840 **Fax** 231.726.5029
www.earthtronics.com

Revised 12/14/2017