

Project	
Date	
Prepared By	
Model #	WPA120WSCCTBK5

Specifications

ELECTRICAL:

Watts: 72W/96W/120W Voltage: 120-347VAC Power Factor: >0.9 Operating Temp. Range: -40°C (-4°F) to 45°C (113°F)

LIGHT:

Lumens:

9360,12480,15600LM

Color Temperature: 3000K,

4000K, 5000K

CRI: 80+

Dimming: 0-10VDC

AGENCY APPROVALS:

DLC® Premium: Yes

UL: Yes IP65: Yes

PRODUCT DETAILS

Finish Color: Bronze

Lens Material:

Polycarbonate, Anti-UV

Warranty: 5 years
Weight: 12.35 LBS

Dimensions:

10.51"L x 5.78"W x 12.85"H



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

LED Adjustable Slim Wall Pack

Color & Wattage Selectable











ORDER CODE:
11628

MODEL NUMBER:
WPA120WSCCTBK5

COLORTEMPERATURE:
3000K, 4000K, 5000K

WATTAGE SELECTABLE
72W/96W/120W
DLC® PRODUCT ID:
PL2L9E73LCKN
REBATE AVAILABILITY*

PRODUCT DESCRIPTION

The EarthTronics LED Adjustable Wall Pack has a slim profile design. It can be locked into any angle ranging from 0° to 90° providing exterior security illumination where required. The durable die cast aluminum housing is powder coated to maintain the fixture appearance for several years. Select from 3000K, 4000K or 5000K color temperatures as well as 9360, 12480 or 15600 lumen levels, this is easily done by the dial switch located on the side of the product. It features a high 80+ CRI providing an excellent light source for nearly any task. The polycarbonate lens provides durability and resistance impact, and the conduit entry points allow direct wall or junction box mounting. These adjustable wall pack fixtures feature 120-277V universal voltage. This fixture can withstand the elements, it's made to last in the outdoors with the IP65 rating and a minimum start temperature of -40°F. They are equipped with a 0 - 10-volt continuous dimming driver with a dimming range capability of 10% to 100%. The long 50,000-hour life is backup with a 10 year limited warranty. The wall pack fixture requires a properly anchored UL recognized junction box for proper installation. Photocell for dusk to dawn operation is installed in this fixture. Night Sky Complaint. DLC® listed product.

PRODUCT FEATURES

- + Color Selectable: 3000K, 4000K, 5000K
- + Wattage selectable: 72, 96, 120
- + Universal Voltage 120-347VAC
- + Adjustable 0-90°
- + Durable die cast aluminum housing
- + 0-10V continuous dimming driver
- + Photocell for dusk to dawn operation

- + Dimming range of 10% to 100%
- + Sealed to and tested for IP65
- + Factory preset to maximum wattage, 5000K
- + Night Sky Complaint
- + DLC® Technical Requirement 5.1

APPLICATIONS

- + Building Exteriors
- + New Construction Buildings
- + Walls
- + Parking Areas
- + Cooridor Lighting

Please consult installation instructions for proper application and use of this fixture.

*Rebate availability access it here: www.earthtronics.com/rebate-finder



LED Adjustable Slim Wall Pack

Color & Wattage Selectable

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Package: 4 Fixture Dimensions:

11.81" L x 6.30" H x 14.17" W

Weight: 14.55 LBS UPC: 840791116289

MASTER CARTON


Individual Package: 1 Fixture Dimensions:


13.39" L x 12.40" H x 14.96" W


Weight: 29 LBS

UPC: 84079111628900

PRODUCT DIMENSIONS







PRODUCT DIMENSIONS

SIDE

