

Project	
Date	
Prepared By	
Model #	HBL9250WH5

Specifications

FI FCTRICAL

Watts: 92

Voltage: 120-347VAC Power Factor: >0.9

THD: ≤10%

Operating Temp. Range: -20°C (-4°F) to 50°C (122°F)

LIGHT

Initial Lumens: 13800 Lumens per Watt: 150 Color Temperature: 5000K

CRI: 82

Dimming: 0-10V Dimmable: Yes

AGENCY APPROVALS

UL: Yes RoHS: Yes

DLC® Premium: Yes

PRODUCT DETAILS

Housing: Steel

Lens: PMMA optical glare-

control lens

Warranty: 5 years

Fixture

Rated Life: 50,000 hours

Lumen Maintenance: L70 at 100,000 hrs

Weight: 7.5 LBS

Dimensions: 16.62"L x 10.25" W x 2.0"D



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

HBL-1 High Bay Premium Series

13800 Lumens, 92 Watt, 5000K, 120-347V



ORDER CODE: 11702

MODEL NUMBER: HBL9250WH5

LENGTH: 1.3 ft

DLC PRODUCT ID:

S-6JG9LO

REBATE AVAILABILITY*

















PRODUCT DESCRIPTION

EarthTronics LED High Bay offers a small, lightweight design that delivers excellent energy savings without sacrificing performance. This 92-watt LED High Bay has a 1.3ft design and provides 13800 lumens. It features a durable steel housing and the 5000K color temperature with a high 80+ CRI providing excellent visual acuity for accuracy when working in manufacturing and warehousing applications. Various mounting options are available.

PRODUCT FEATURES

- + Lightweight, compact design
- + 120-347VAC 50-60Hz
- + Operating at 150 lumens per watt
- + 6kV ANSI surge protection standard
- + Integral LED lens is constructed from PMMA and provides even illumination across the face of the high bay
- + Durable steel housing
- + Up to 50°C true ambient temperature
- + 6ft 18/3 SJT cord sold separately (see available options)

- + DLC® Premium
- + Driver standard with 0-10V dimming (prewired)
- + Suitable for damp locations
- + Dimmable
- + 100,000 hours rated life L70
- + Hanging hardware included V-Hooks &
- + Emergency back-up driver available
- Compatible with EarthConnect® Network Lighting Controls

APPLICATIONS

- + Manufacturing Facility
- + Auditorium

- + Warehouse
- + Cafeteria
- + Gymnasium

Please consult installation instructions for proper application and use of this fixture.

*Rebate availability access it here: www.earthtronics.com/rebate-finder



LED High Bay Fixture

13800 Lumens, 92 Watt, 5000K, 120-347V

PACKAGE DETAILS

Individual Carton Qty: 1

Dimensions:

17.28" L x 10.5" W x 2.00" H


Weight: 7.5 LBS UPC: 840791117026 Master Carton Qty: 4

Dimensions:

17.5" L x 11.0" W x 9.0" H


Weight: 30 LBS UPC: 84079111702600


PRODUCT DIMENSIONS




Average Illuminance: 30 fc Number of Luminaires: 4 Workplane Height: 2.5 ft

LIGHTING LAYOUT





Pendant Hanger Order Code: 11711




Surface Mount Order Code: 11710



Wire Guard Order Code: 11712



12VDC PIR Motion Sensor Order Code: 11709 Remote Order Code: 11810



External Emergency Back up Kit (30W) Order Code: 11617

6ft 18/3 SJT cord available (sold separately)

OPTIONAL ACCESSORIES

Order Code: 11836 6ft 18/3 SJTOOW 300V Cord - White (cord only)

Order Code: 11837 6ft Cord (18/3 SJT White) with 5-15P 120V 15AMP Plug

Straight Blade Plug - Black

Order Code: 11838 6ft Cord (18/3 SJT White) with NEMA L7-15P 277V 15AMP

Twist Lock Plug - Black

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: Rebate Finder - Linear LED Highbay

www.earthtronics.com/rebate-finder/catalog/





