

Project	
Date	
Prepared By	
Model #	LW2WSCCTD5S

Specifications

ELECTRICAL

Watts: 15, 20, 25

Voltage: 120-347VAC

Power Factor: >0.9

THD: <10%

Working Temp. Range:
-4°F to 104°F

LIGHT

Lumens:

1725, 2300, 2875

LPW: 115

Color Temperature:

3500K, 4000K, 5000K

CRI: >80

AGENCY APPROVALS

DLC®: Yes

FCC: Yes

UL: Yes

PRODUCT DETAILS

Housing: Acrylic

Warranty: 5 years

Fixture

Rated Life: 50,000 hours

Weight: 2.42 lbs

Lumen Maintenance:


L70 at 50,000 hrs

Dimensions:

23.77"L x 5.39"W x 2.20"H

LED Wrap Fixture 24"

Color and Wattage Selectable



ORDER CODE:

11905

MODEL NUMBER:

LW2WSCCTD5S

COLOR SELECTABLE:

3500K, 4000K, 5000K

LUMEN LEVEL:

1725 lumens - 15 watts

2300 lumens - 20 watts

2875 lumens - 25 watts

DLC® PRODUCT ID:

S-3GP19W

PRODUCT DESCRIPTION

EarthTronics LED 2 ft. wrap fixtures are designed to meet low light egress requirements and costs efficient. Select from 3500K, 4000K or 5000K color temperatures as well as 1725, 2300 or 2875 lumen levels as this product is color and wattage selectable. This LED 2 ft. wrap light features impact resistant UV stable acrylic lens, and a steel housing with a white finish. This fixture offers simple installation on existing junction boxes, and operates at 120-347VAC. The LED wrap fixture is a perfect solution for offices, stairways, bathrooms, and storage areas.

PRODUCT FEATURES

- + Color selectable: 3500K, 4000K, 5000K
- + DLC® Technical Requirement 5.1
- + 110° beam angle with use of frosted acrylic lens
- + 50,000 hour rated life
- + UL 1598 suitable for damp locations
- + Ideal replacement for less efficient fluorescent wrap fixtures
- + Great for low traffic areas
- + 0-10 volt dimming, 120-347VAC

APPLICATIONS

- + Offices
- + Multipurpose Rooms
- + Schools
- + Conference Rooms
- + Hallways
- + Workshops
- + Stairwell
- + Corridors
- + Storage areas

Please consult installation instructions for proper application and use of this fixture.

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Carton Qty: 1

Dimensions:

25.75" L x 7.28" W x 4.09" H

Weight: 2.42 lbs

UPC: 840791119051

MASTER CARTON

Master Qty: 8


Dimensions:

26.33" L x 15.24" W x 17.4" H

Weight: 21.1 lbs

UPC: 84079111905100

PRODUCT DETAILS



23.77" L x 5.39" W x 2.20" H

OPTIONAL ACCESSORIES

- Emergency backup driver
- Microwave Occupancy Sensor & Remote Control
- Harness & Joint Kit
- Vhooks & Chain

NETWORK LIGHTING CONTROLS (NLC)



Compatible with



Order Code: 11803
Low Bay Microwave Sensor



Order Code: 11804
Bluetooth[®] Mesh / Single Channel Fixture
Controller Sensor Ready

EarthConnect, Bluetooth[®] networked lighting control system makes it easy to maximize energy savings, achieve code compliance for indoor applications. It's simple and intuitive. Using the EarthConnect app, nodes can be commissioned without the need for a gateway or Internet access.

For more information visit:

<https://www.earthtronics.com/product/earthconnect.com>

