

| | |
|-------------|----------------|
| Project | |
| Date | |
| Prepared By | |
| Model # | LT878CCTABSDE2 |

Specifications

ELECTRICAL

Watts: 7.5 Watt Lamp,
9W System

Voltage: 120-277VAC

Power Factor: >0.9

Operating Temp. Range:
-4°F - 113°F

Base Type: G13

Dimmable: Yes

Beam Angle: 220°

LIGHT

Initial Lumens: 1150

Lumens per Watt: 153

Color Temperature:

3000K,
3500K,4000K,5000K, or
6500K

CRI: >80

AGENCY APPROVALS

RoHS: Yes

FCC: Yes

NSF: Yes

UL: Yes

PRODUCT DETAILS

Enclosure Material:

Glass

Endcap Material:

Plastic

Warranty: 5 years

Fixture

Rated Life: 50,000 hours

Type A/B Hybrid - 2ft

Type A/B, For Single or Double End Installation



ORDER CODE:

11919

MODEL NUMBER:

LT878CCTABSDE2

WATTS: 7.5 Watt

COLOR TEMPERATURE:

3000K,3500K,4000K,
5000K or 6500K

LUMENS:

1150 Lumens

PRODUCT DESCRIPTION

EarthTronics UL Type A/B 2FT LED T8 Lamp is a retrofit direct wire tube for single or double end installations. It is a universal solution that can be used with Type A and Type B T8 lamps. Type A is a plug and play solution that can work on electronics ballasts and Type B can be direct wired quickly, no lamp holder modifications necessary. This lamp is color selectable, offering 5 choices 3000K, 3500K, 4000K, 5000K or 6500K which can be adjusted in the field by just sliding the switch to your desired color. This is an excellent option for those that want a fast installation with the ballasts and have a backup plan if the ballast fails. It provides exceptional LED lighting with reduced energy and maintenance costs. This lamp also works with shunted and non-shunted sockets, dry or damp locations and enclosed fixtures. The beam angle provides a wide distribution pattern and is perfect for directing more light to the working surface from existing troffer fixtures and strip fixtures as well as task and display lighting applications. Perfect for replacement of T8 fluorescent tubes. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. 120/277V operation.

PRODUCT FEATURES

- + Easily retrofit T8, 4 foot tubes
- + Provides 1150 lumens
- + Flexible design allows for single end or double-end operation on 120-277V
- + Suitable for dry and damp locations
- + Type A: Plug & Play - can be installed on electronic ballast
- + Works with both shunted and non-shunted sockets
- + Type B: Direct wire without modifying lamp holders
- + Suitable for enclosed fixtures

*Ballast Compatibility Listing can be found here: [11919 Compatibility List](#)

Please consult installation instructions for proper application and use of this fixture.

*Rebate availability access it here: www.earthtronics.com/rebate-finder