# LED MR16

2.0 in

Electrical

Input Current

Power Factor

Voltage

Temp

Light

(CRI)

UL

RoHS

Base Type

Initial Lumens

Lumens per Watt

Color Temperature

Color Rendering

Agency Approvals

Beam Angle

Rated Hours

Frequency

Min. Start Temp

Max. Operating

Watt

1.89 in

6.5

78 (mA)

> 0.50

12 volt

60hz

-4F

104F

GU5.3

500 77

5000K

80

38°

Yes

25,000 hr rated

Yes





6.5 watt MR16 EarthBulb LED bulb replaces 50 watt incandescent lamp for over 70% energy savings. 5000K daylight with 38 degree beam angle. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power, multi-chip LED and an advanced cooling system provides for 25,000 hours of LED life.


## **PRODUCT FEATURES**

- GU5.3 pin base is standard
- Provides 500 lumens, Capable of dimming to less than 5%
- Chipset provides 5000K daylight with a high color rendering
- No Mercury, RoHS Certified

# CONE OF LIGHT



Y(



## LUMINOUS DISTRIBUTION INTENSITY DATA


C(deg)					
(deg)	0	23	45	68	90
0	948	946	944	942	941
5	880	892	894	890	888
10	754	764	765	767	758
15	585	601	605	592	570
20	396	405	407	394	365
25	226	234	227	213	193
30	113	115	110	104	92.7
35	55.4	55.6	54.2	50.8	45.3
40	29	29.3	28	26.6	24.8
45	17.8	17.7	17.2	16.7	15.9
50	12.7	12.5	12.2	12	11.7
55	9.88	9.61	9.55	9.56	9.43
60	8.29	8.01	7.99	8.06	8.02
65	7.09	6.77	6.85	6.88	6.81
70	6.05	5.75	5.74	5.83	5.72
75	5.03	4.68	4.65	4.8	4.61
80	3.82	3.48	3.37	3.56	3.28
85	2.28	2.07	1.95	2.03	1.71
90	0.55	0.55	0.47	0.39	0.14

## MODEL NUMBER: LMR16650D5





## LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



#### AVERAGE BEAM ANGLE (50%):33.9°

Note: IES files available upon request.



		WODEL NUWDER: LWR 10030D3									
FCC	Yes	Order Code	Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty			
Product Details						α.,		α.,			
		10278	1	840791102787	00840791102787	6	84079110278700	24			
Warranty	10 years, 6 hrs/day	Dimensions (inches - Length x Width x Height)									
Mercury Content	0	10278	1	2.17 x 2.17 x 3.15	7.13 x 5 x 3.81	6	10.39 x 14.65 x 4.37	24			
Diameter	2.0"	Weight (lbs)									
Overall Length	1.89"	10278	1	0.154	1.1	6	4.73	24			

