PAR30



Electrical				
Watt	14			
Input Current	140 (mA)			
Power Factor	0.96			
Voltage	120 volt			
Frequency	60hz			
Min. Start Temp	-4F			
Max. Operating Temp	104F			
Base Type	E26 Medium			
Light				
Initial Lumens	850			
Lumens per Watt	61			
Color Temperature	3000K			
Color Rendering (CRI)	83			
Beam Angle	40°			
Agency Approvals				
UL	Yes			
Energy Star	40,000 hr rated			
RoHS	Yes			
FCC	Yes			
Product Details				
Warranty	10 year, 6 hrs/days			
Mercury Content	0			
Diameter	3.74"			
Overall Length	4.61"			

14 Watt 3000K PAR30 LED



PRODUCT DESCRIPTION

14 watt PAR30 EarthBulb LED floodlight replaces 75 watt incandescent floodlights for over 80% energy savings. 3000K color of light is standard. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 40,000 hours of LED life. Medium screw base.

PRODUCT FEATURES

- Dimming PAR30 flood light provides 850 lumens, capable of dimming to less than 5%
- 40° beam angle provides a flood, not spot light
- Lensed single chip design look like halogen when powered on
- Chipset provides 3000K white light with a high color rendering rating over 80
- Wet locations rated

CONE OF LIGHT

Lumens: 850					
Distance ft	Foot Candles fc	Diameter ft			
2	367.6	1.32			
4	91.9	2.64			
6	40.85	3.96			
8	22.98	5.28			
10	14.70	6.6			
UMBIGUE DISTRIBUTION INTENSITY DATA					


PRODUCT APPLICATIONS



LUMINOUS DISTRIBUTION INTENSITY DATA

ls-					
C(deg)					
Y(deg)	0	23	45	68	90
0	1644	1645	1646	1646	1646
5	1505	1498	1498	1505	1517
10	1210	1194	1191	1202	1228
15	918	897	893	906	932
20	652	637	633	643	658
25	448	440	436	436	441
30	323	318	313	309	308
35	235	231	226	221	216
40	164	161	155	149	145
45	109	107	103	97.7	93.2
50	70.6	69.4	66.2	63.2	61.1
55	47.9	47.5	45.9	43.8	42.3
60	33.1	33.3	32.9	32.1	31.5
65	24.9	25.4	25.2	24.8	24.3
70	18.7	19.1	19.2	18.9	18.5
75	13.2	13.6	13.9	13.9	13.7
80	7.99	8.23	8.42	8.56	8.46
85	3.33	3.47	3.58	3.69	3.66
90	0	0	0	0.01	0


LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):34.3°

Note: IES files available upon request.

Order Code	Individual UPC	Master Park UPC	Qty		
19191	8 11180019191	008 11180019191	6		
Dimensions (inches)					
19191	4.06 x 4.06 x 6.30	8.71 x 13.07 x 6.97	6		
Weight (lbs)					
19191	0.726	4.862	6		



Individual





