

Project	
Date	
Prepared By	
Model No.	LP16630D8

# Specifications

#### FI FCTRICAL

Watts: 6.5

Input Current: 69 (mA)
Power Factor: 0.8
Voltage: 120 volt, 60Hz

Base Type: E26 Medium Operation: Dimmable

Operating Temp. Range:

-4°F to 104°F

#### **LIGHT**

Initial Lumens: 500 Lumens per Watt: 76.9 Color Temperature: 3000K

**CRI**: 84

#### **AGENCY APPROVALS**

UL/FCC : Yes Energy Star: Yes

RoHs: Yes

#### PRODUCT DETAILS

Warranty: 3 years Rated Life: 15,000 hrs.

Dimensions: Length: 2.76" Diameter: 1.96"



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

# LED PAR16

500 Lumen, 6.5 Watt, 3000K



**ORDER CODE:** 

11720

**MODEL NUMBER:** 

LP16630D8

**OPERATION:** 

Dimmable

**ENERGY STAR ID:** 

2404351

REBATE AVAILABILITY\*

#### PRODUCT DESCRIPTION

6.5 watt PAR16 EarthBulb LED floodlight replaces 50 watt incandescent floodlights for over 80% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. PAR16 can be used indoor or outdoor.

#### PRODUCT FEATURES

- + This PAR16 provides 500 lumens
- + Dimming to less than 10%
- + Energy Star rated product
- + Suitable for damp locations
- + 3000K white light with a high color rendering rating 80+

#### **APPLICATIONS**

- + Recessed Can fixtures
- + Track Lighting
- + Display Lighting
- + Corridor Lighting
- + Large hanging pendants

### PACKAGE DETAILS

#### INDIVIDUAL PACKAGE

Individual Carton Oty: 1
Dimensions:

2.00" L x 2.00" L x 2.87" H UPC: 840791117200

#### **INNER CARTON**

Master Carton Oty: 12

Dimensions:

8.50" L x 6.42" W x 3.43" H UPC: 84079111720000

## MASTER CARTON

Master Carton Oty: 48

Dimensions:

13.22" L x 8.56" W x 7.40" H **UPC**: 84079111720000







