

# LED Plug In

## 11.5 Watt 4000K 2-Pin LPD11M/G24d/840 LED Plug In



### PRODUCT DESCRIPTION

EarthTronics 11.5 watt LED, LPD11M/G24d/840 easily replaces 18 watt G24d-2 base compact fluorescent lamps and provides 33% energy savings. It is physically the same form factor as the CFQ18W/G24d that it replaces. This 2-pin lamp produces 1100 lumens and works directly on the existing magnetic ballast. No rewiring necessary. Instant on, no warm up time and a long service life make this lamp an easy choice in many applications. Available colors include 3000K, 4000K and 5000K and the CRI rating is >80. The unique design illuminates nearly identically to the bulb it replaces and can be used in any rotation or orientation in open fixtures. The 25,000 hour rated life provides 3 times the service life of a typical compact fluorescent lamp. For use only on single lamp ballast. Not for use in enclosed fixtures.

### PRODUCT FEATURES

- Same form factor as the PL lamp it replaces.
- Light distribution pattern is nearly identical to PL lamps.
- Works directly on magnetic ballasts for easy “plug & play” installation.
- LED provides instant on and full brightness – no waiting.
- Also available in 3000K and 5000K color temperatures.

### Applications:

- Recessed downlights
- Wall sconce
- Vanity fixtures
- Surface mount ceiling & wall fixtures
- Outdoor post lamps
- Outdoor flood lights

### Ordering Code:

- 10178
- 12 pack inner, 48 pack master

### Model:


- LPD11M/G24d/840

### Replaces:

- GE F18DBX/840/ECO
- Philips PL-C18W/840/Alto
- Sylvania CF18DD/840
- Any PL lamp utilizing the G24d-2 base, 2-pin

### Cautions:

- Not for use on 2 lamp ballast. Intended for 1 lamp per ballast.
- Not for use in enclosed fixtures.
- This 2-pin LED lamp is intended for use on Magnetic ballast.
- Not for use with dimmer controls.
- Not for use with emergency lighting.



G24d-2 base, 2-pin

Electrical	
Watt	11.5 watt
Power Factor	> 0.50
Ballast required	Magnetic
Base Type	G24d-2, 2-Pin
Min. Start Temp	0° F
Max. Operating Temp	120° F
Light	
Initial Lumens	1100
Lumens per Watt	95 lpw
Color Temperature	4000K
Color Rendering (CRI)	82
Beam Angle	Full radial
Agency Approvals	
UL	Yes
RoHS	Yes
FCC	Yes
Product Details	
Warranty	10 years, 6 hours per day
Mercury Content	No Hg
Overall Length	6.6"