# LED PAR30



Electrical				
Watt	14			
Input Current	140 (mA)			
Power Factor	0.96			
Voltage	120 volt			
Frequency	60hz			
Min. Start Temp	-4F			
Max. Operating Temp	104F			
Base Type	E26 Medium			
Light				
Initial Lumens	850			
Lumens per Watt	61			
Color Temperature	4000K			
Color Rendering (CRI)	83			
Beam Angle	40°			
Agency Approvals				
UL	Yes			
Rated Life	40,000 hr rated			
RoHS	Yes			
FCC	Yes			
Product Details				
Warranty	10 years, 6 hrs/day			
Mercury Content	0			
Diameter	3.74"			
Overall Length	4.61"			

# 14 Watt 4000K PAR30 LED



#### PRODUCT DESCRIPTION

14 watt PAR30 EarthBulb LED bulb replaces 75 watt incandescent floodlights for over 80% energy savings. 4000K color of light. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 40,000 hours of LED life. Medium screw base.

## **PRODUCT FEATURES**

- Dimming PAR30 flood light provides 850 lumens, capable of dimming to less than 5%
- 40° beam angle provides a flood, not spot light
- Lensed single chip design look like halogen when powered on
- Chipset provides 4000K white light with a high color rendering rating over 80
- · Wet locations rated

# **CONE OF LIGHT**

Lumens: 850			
Distance	Foot Candles	Diameter	
ft	fc	ft	
2	367.6	1.32	
4	91.9	2.64	
6	40.85	3.96	
8	22.98	5.28	
10	14.70	6.6	


### PRODUCT APPLICATIONS



#### **LUMINOUS DISTRIBUTION INTENSITY DATA**

C(deg)					
Y(deg)	0	23	45	68	90
0	1644	1645	1646	1646	1646
5	1505	1498	1498	1505	1517
10	1210	1194	1191	1202	1228
15	918	897	893	906	932
20	652	637	633	643	658
25	448	440	436	436	441
30	323	318	313	309	308
35	235	231	226	221	216
40	164	161	155	149	145
45	109	107	103	97.7	93.2
50	70.6	69.4	66.2	63.2	61.1
55	47.9	47.5	45.9	43.8	42.3
60	33.1	33.3	32.9	32.1	31.5
65	24.9	25.4	25.2	24.8	24.3
70	18.7	19.1	19.2	18.9	18.5
75	13.2	13.6	13.9	13.9	13.7
80	7.99	8.23	8.42	8.56	8.46
85	3.33	3.47	3.58	3.69	3.66
90	0	0	0	0.01	0


#### **LUMINOUS DISTRIBUTION INTENSITY DIAGRAM**



# AVERAGE BEAM ANGLE (50%):34.3°

Note: IES files available upon request.

MODEL NUMBER: L3FP314DW					
Order Code	Individual UPC Master Park UPC		Qty		
19832	8 11180019832	008 11180019832	6		
Dimensions (inches)					
19832	4.06 x 4.06 x 6.30	8.71 x 13.07 x 6.97	6		
Weight (lbs)					
19832	0.726	4.862	6		



Individual





