

Project	
Date	
Prepared By	
Model #	LT815840SEDEC

Specifications

ELECTRICAL

Watts:
15 watt lamp

Voltage:
120-277V 50/60Hz

Power Factor: >0.9

Operating Temp. Range:
-20°C to 45°C

Base Type:
G13 Medium Bi-pin

Dimmable: Yes

Dimming Type: Phase-cut

Dimming Range: 10-100%

LIGHT

Initial Lumens: 2200

Lumens per Watt: 147

Color Temperature:
4000K

CRI: >82

AGENCY APPROVALS

UL/FCC: Yes

RoHS/NSF: Yes

DLC® Listed: Yes

PRODUCT DETAILS

Diffuser Type:
Internal coated glass tube

Warranty: 5 years
Fixture
Rated Life: 50,000 hours

Dimensions:
1" Diameter
48" Length

LED Linear Tube 48" - Coated

Type B, 2200 Lumens, 15 Watt, 4000K



ORDER CODE:

11124

MODEL NUMBER:

LT815840SEDEC

PRODUCT ID:

S-AZ20XR

*Rebate Availability

PRODUCT DESCRIPTION

EarthBulb direct wire LED linear T8 lamps eliminate the need for electronic ballast or drivers for maximum energy savings. This 4000K color temperature lamp consumes only 15 watts to produce 2200 lumens. A high Color Rendering Index (CRI) of 82 insures excellent color clarity. The 300 degree beam angle provides a wide distribution pattern and is perfect for directing more light to the working surface from existing troffer fixtures and strip fixtures as well as task and display lighting applications. Perfect for replacement of T8 fluorescent tubes. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. This lamp features a flexible design allowing for single-end or double-end operation on 120-277V. To install, simply remove the existing fluorescent ballast and direct wire the line voltage. Direct wire quickly, no lamp holder modifications necessary, just run the black (load) to the one end and white (neutral) to the other. Shatterproof coated to conform to the Food Safety standards. Operates on 120-277V.

PRODUCT FEATURES

- + Easily retrofit T8, 4 foot tubes
- + Provides 2200 lumens
- + Flexible design allows for single-end or double-end operation on 120-277V
- + 4000K natural white with a high color rendering rating of 82
- + Direct wire without modifying lamp holders
- + Conforms to UL Standard 1993 and 1598C. Certified to CSA Standard C22.2 No. 1993 & C22.2 No. 250.1
- + This type B lamp is double end direct wire so no lamp holder modifications
- + Shatterproof coated to conform to the Food Safety standards

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Carton Qty: 1
Dimensions: 48" Length x 1.2" Width x 1.2" Height
Weight: .53 lbs
UPC: 840791111246

MASTER CARTON

Master Carton Qty: 25
Dimensions: 49.7" Length x 6.5" Width x 7.5" Height
Weight: 14.4 lbs
UPC: 84079111124600

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: [Rebate Finder – Linear Tube](#)

www.earthtronics.com/rebate-finder/catalog/

