Downlight Fixture



| Electrical | | | | |
|-------------------------------|--------------------------------------|--|--|--|
| Watt | 9 | | | |
| Voltage | 120 V | | | |
| Power Factor | >0.9 | | | |
| Min. Start Temperature | -40°F | | | |
| Max. Operating Temperature | 135°F | | | |
| Light | | | | |
| Initial Lumens | 700 | | | |
| Lumens per Watt | 78 | | | |
| Color Temperature | 5000K | | | |
| Color Rendering (CRI) | 80+ | | | |
| Agency Approvals | | | | |
| FCC | Yes | | | |
| ETL | Yes | | | |
| Product Details | | | | |
| Warranty | 5 year (based on 6 hours/ day) | | | |
| Rated Life | 40,000 hours | | | |

LED 6 Inch Downlight Fixture EarthTronics 700 Lumens 9 Watt 5000K




PRODUCT DESCRIPTION

6" IC-Rated LED Recessed Downlight Fixture can be easily installed in finished drywall or architectural tile ceilings in facilities such as schools, hospitals, office buildings and other commercial and residential applications. This fixture provides 78 lumens per watt with a high 80+ CRI for improved visual acuity and efficient performance. It features smooth dimming down to five percent on typical incandescent dimmer controls. IC-rated for use in insulated ceilings and meets IECC air leakage requirements to provide a versatile and attractive downlight product. The UL Wet Location listing makes this product a perfect solution for high humidity areas and bathroom showers found in long-term care facilities, as well as hotel guest rooms. These fixtures are designed for easy installation and provide an attractive step baffle trim to provide a proper cut-off angle. For use on 120VAC power supplies.

PRODUCT FEATURES

- Advanced design IC rated recessed downlight
- Easy clip installation in drywall or suspension ceilings
- 3000K, 4000K, 5000K colors available with high 80+ CRI
- 40,000 hour rated life
- 120VAC, dimmable down to 5%



ORDER CODE: RTF700506WH2 **MODEL NUMBER: RTF700506**

| Individual | Name 1 | |
|-----------------|--------|------|
| | _ | |
| Mostor Dook LIC | 00 | Otre |

| Order Code | Pack Size | Individual UPC | Master Pack UPC | Qty | | |
|---|-----------|--------------------|----------------------|-----|--|--|
| RTF700506WH2 | 1 | 840791106099 | 84079110609900 | 6 | | |
| Dimensions (inches - Length x Width x Height) | | | | | | |
| RTF700506WH2 | 1 | 7.86 x 3.91 x 7.93 | 16.41 x 12.59 x 9.01 | 6 | | |
| Weight (lbs) | | | | | | |
| RTF700506WH2 | 1 | 0.96 | 9.6 | 6 | | |

CAUTION: If the fixture is to be removed or replaced, please ensure that they electricity is switched off and that the fitting is cool before touching it.





