

# UFO Highbay LED

A full family of products easily replace up to 400 watt HID fixtures. DLC Premium Performance.

## Key Features

- + Easily replace up to 400 watt H.I.D. Highbay fixtures
- + Unparalleled cool operation fixture is fabricated from 1060 high stamped aluminum purity (99.6% pure)
- + Thermal conductivity exceeds 200W/M\*K (die cast 60-90W/M\*K and aluminum extrusion typically 180W/M\*K)
- + Standard 120° beam angle
- + IP65 rated for wet location use
- + Ships standard with 6 foot 300V 18/3 SJT and mounting ring
- + 13,000 to 33,000 lumen available
- + 120/277V and 347/480V premium quality drivers available
- + 0-10V dimming is standard



## DESCRIPTION

EarthTronics HBU Series LED High Bay available in 4000K and 5000K, offering a true “one-for-one” LED alternative for any commercial or industrial space requiring a high lumen light source for high ceilings. The HBU Series delivers a higher lumen per watt output with world-class Seoul chips, Mean Well drivers and DLC Premium certification that meets even higher efficacy and lumen maintenance requirements than past high bay models.

The lightweight design and the standard mounting hook with a safety screw enable quick installation and retrofitting of interior spaces. The fixtures are stamped from 96% pure aluminum in a unique design and size that maximizes cooling providing a long life product with high lumen maintenance.

The HBU Series LED High Bay features an IP65 wet location use rating for exposed environments and are shipped complete with a 6' cord to enable easy installation. The LED driver is full functioning with 0-10V dimming on all models and is standard for 100 -277V operation. A 347-480V full functioning driver is available as well. The HBU series is DLC listed and provides a long-lasting, 50,000-hour life. The fixture can be easily installed to work on existing control systems.

## OPTIONS AVAILABLE

- + 60° Polycarbonate Prismatic shade
- + 70° Aluminum Shade

## SPECIFICATONS & CERTIFICATIONS



## APPLICATIONS

- + Manufacturing Facility
- + Cafeteria
- + Auditorium
- + Gymnasium
- + Warehouses

## DLC PREMIUM PERFORMANCE

EarthTronics selected world-class Seoul chips and engineered performance to meet and exceed DLC premium standards. The UFO housing exceeds 200W/M\*K (that's the ability to remove 200 watts of heat energy per meter kelvin) which enables its long life.

## OPERATION

Standard UFO highbay is 100 – 277 VAC and 240 – 480 VAC is available. All models include 0-10V dimming. The IP65 rating allows these fixtures to operate in adverse warehouse and manufacturing applications.

## PRODUCT OFFERING

Lumen	Wattage	Color Temp	CRI
13200LM	100W	4000K	80+
13500LM	100W	5000K	80+
20100LM	150W	4000K	80+
20550LM	150W	5000K	80+
26400LM	200W	4000K	80+
27000LM	200W	5000K	80+
31920LM	240W	4000K	80+
32640LM	240W	5000K	80+