

Project	
Date	
Prepared By	
Model #	LT840840BDEC

Specifications

ELECTRICAL

Watts:

40 watt lamp

Voltage:

120-277V 50/60Hz

Power Factor: >0.9

Operating Temp. Range:

-20°C to 45°C

Base Type: FA8 1Pin

LIGHT

Initial Lumens: 5500 Lumens per Watt: 138 ColorTemperature: 4000K

CRI: >82

AGENCY APPROVALS

UL/ETL: Yes FCC: Yes RoHS: Yes DLC®: Yes

PRODUCT DETAILS

Warranty: 10 years

Fixture

Rated Life: 50,000 hours

DiffuserType:

Internal coated glass tube

Dimensions: 1" Diameter 96" Length



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

LED Linear Tube 96" - Coated

Type B, 5500 Lumens, 40 Watt, 4000K





ORDER CODE:

11636

MODEL NUMBER: LT840840BDEC

LENGTH: 96 Inch

Type B

DLC PRODUCT ID: PL1XAIB9DIIN

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

Easily replace T12 and T8 96" fluorescent lamps and save up to 65%* in energy costs. The EarthTronics 96" TLED provides 5500 lumens and consumes only 40 watts. The lamp CCT is 4000K and provides 82CRI for improved visual acuity and color clarity when compared to the fluorescent lamps being replaced. The construction is glass and the light distribution is 300° which makes the lamp an easy answer when retrofitting simple strip fixtures or more decorative pendant fixtures. This Type B "double end" direct wire lamp is easily installed with simple rewiring directly to 120VAC or 277VAC power supply. Follow the instructions provided to wire the load (black wire) to one end of the lamp and the neutral (white wire) to the other end. There is no need to replace lamp holder sockets. The EarthTronics 96" TLED is a perfect for use in schools, institutions, warehouses, retail and other commercial applications where energy savings is required. 50,000 hour rated life. Fa8 lamp base type. Operates on 120 – 277VAC.

*when replacing a 72 watt T12 fluorescent

PRODUCT FEATURES

- + Easy installed "double end" direct wire T8
- + Direct wire eliminates the need for electronics ballast or drivers
- +4000K cool white light with a high color rendering rating of 82
- +DLC® technical requirement version 5.1

- + 120-277VAC 50/60Hz
- + Provides 5500 lumens
- + Conforms to UL Standard 1993 and 1598C. Certified to CSA Standard C22.2 No. 1993 & C22.2 No. 250.1

Please consult installation instructions for proper application and use of this fixture.

*Rebate availability access it here: www.earthtronics.com/rebate-finder



EarthTronics. LED Linear Tube 96"- Coated

Type B, 5500 Lumens, 40 Watt, 4000K

PACKAGE DETAILS

MASTER CARTON


Master Carton Oty: 10

Dimensions: 97.7" Length x 7.7" Width x 5.88" Height


Weight: 11.91 lbs UPC: 84079111636400

LAMP BASETYPE

OPTIONAL ACCESSORIES - (Sold separately)



FA8 1Pin



External Emergency Backup Kit


Order Code: 11405

Dimensions:

23.97" Length x 23.97" Width x 2" Depth

Weight: 6.75 LBS UPC: 84079112526

WIRING DIAGRAM



Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: Rebate Finder - Linear Tube











www.earthtronics.com/rebate-finder/catalog/