LED Wall Pack



Electrical	
Watt	75
Voltage	347 Volt
Power Factor	>0.9
Min. Operating Temperature	-40°C
Light	
Initial Lumens	9000
Lumens per Watt	120
Color Temperature	4000K
Color Rendering (CRI)	80+
Beam Angle	120°
Agency Approvals	
IP65	Yes
RoHS	Yes
ETL	Yes
Product Details	
Housing Material	Aluminum
Lens Material	Glass
Warranty	5 years, 10 year limited
Rated Life	50,000 hours

LED Traditional Wall Pack 347 **EarthTronics**. 9000 Lumens 75 Watt 4000K

PRODUCT DESCRIPTION

EarthTronics Traditional LED Wall Packs provide exterior, wide-flood area illumination for commercial, industrial and municipal facilities. Available in 75 watt with 4000K color of light, these fixtures provide 9000 lumens. The 75 watt models are built in a standard size 14.6"x7.9"x9.5" aluminum alloy housing with a standard bolt pattern. The WP5-Series LED Traditional Style Wall Pack uses industry-leading LED chips and drivers to deliver a quality, energy saving lighting solution. The 4000K color temperature offers building managers the opportunity match existing HID lamps and to reduce the blue light spectrum often associated with higher color temperatures. Each of the EarthTronics Wall Packs accepts 347 volt AC power supply. The wall packs provide more than 100 lumens per watt and a high 80+ CRI for improved visual acuity and efficient performance. A dusk to dawn sensor is available and is easily added at the time of installation. The design is built to withstand all climates and allows for an extreme temperature range, even operating down to -40 degrees C°, and is IP65 approved for outdoor wet applications. With rated life of 50,000 hours, the WP5 wall pack series is designed for easy installation, directly fitting onto existing electrical boxes, making it the contractor's choice when replacing older highpressure sodium and metal halide wall packs.

PRODUCT FEATURES

- + Easily replace existing wall packs for wide area illumination
- + Tempered and impact resistant clear prismatic borosilicate glass lens
- + Die cast aluminum housing provides long life in commercial installations
- + 0-10v dimming
- + 120° light pattern provides for wide flood distribution
- + 4000K 80CRI is standard
- + IP65 rated for outdoor use
- + Photocell available and easily installed
- + 50,000 hour rated life

Order Code: 11219 Model #: WPT900040BK3

UPC: 840791112199

14.22" 9.26[°]

Dimensions:

14.22 inches x 7.64 inches x 9.26 inches

CAUTION : If the fixture is to be removed or replaced, please ensure that they electricity is switched off and that the fitting is cool before touching it

