LED Floodlight

LED Floodlight 80W 7392 Lumens 5000K





Electrical	
Watt	80
Voltage	120-277V
Power Factor	>0.9
Min. Start Temperature	-40°F
Max. Operating Temperature	135°F
Light	
Initial Lumens	7392
Lumens per Watt	92
Color Temperature	5000K
Color Rendering (CRI)	80+
Agency Approvals	
DLC	Yes
FCC	Yes
ETL	Yes
Product Details	
Housing Material	Aluminum
Lens Material	Tempered Glass
Warranty	5 year (10 year limited)
Rated Life	50,000 hours

PRODUCT DESCRIPTION

The EarthTronics LED Floodlight provides security and general area illumination directed where required. Removable back cover provides easy installation. Textured architectural bronze powder coat finish with tempered glass lens. This 80 watt floodlight operates at 92 lumens per watt efficiency and provides 7392 lumens. 5000K color of light and the high 80+ CRI provide bright illumination. Accepts 120 – 277 volt AC power supply. The long 50,000 hour is backed up with a 5 year warranty.

PRODUCT FEATURES


- 50,000 hour rated life
- 5 year, 10 year limited
- 120/277VAC (347VAC available)
- 5000K available, CRI>80
- Suitable for wet locations
- Removable back cover for easy installation
- Ships standard with yoke mount

ORDER CODE: FL04780050BKY1

MODEL #: FL04780050BKY1

UPC: 840791108451

DLC PRODUCT ID: PLXUR00RHT32



CAUTION: If the fixture is to be removed or replaced, please ensure that they electricity is switched off and that the fitting is cool before touching it



