# LED Linear Tube

2200 Lumen T8 LED 5000K 48 inch Type B Double End for Direct Wire - Coated





Electrical	
Watt	15
Power Factor	> 0.90
Total Harmonic Distortion	< 23%
Voltage	120/277VAC 50/60Hz
Base Type	G13
Operating Temperature Range	-20°C to 45°C
Light	
Initial Lumens	2200
Lumens per Watt	146
Color Temperature	5000K
Color Rendering (CRI)	82
Beam Angle	300°
Agency Approvals	
ETL	Yes
DLC	Pending
RoHS	Yes
FCC	Yes, FCC 47 Part 18 CLASS A
Product Details	
Warranty	5 years, 10 year limited
Mercury Content	0
Diameter	1"
Nominal Length	48"
Rated Life	50,000 hours

#### **PRODUCT DESCRIPTION**

15 watt EarthBulb direct wire LED linear T8 eliminates the ballast for maximum energy savings. Available in 5000K with 300 degree beam angle. Great light output and perfect for replacement of T8 fluorescent tubes. This linear tube provides 2200 lumens and has a CRI of 82. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. To install, simply remove the existing fluorescent ballast and direct wire the line voltage. Direct wire quickly, no lamp holder modifications necessary, just run the black (load) to the one end and white (neutral) to the other. This product is shatterproof coated. Operates on 120-277V.

### PRODUCT FEATURES

- Easily retrofit T8, 4 foot tubes
- Direct wire without modifying lamp holders
- 120/277VAC 50/60Hz, direct wire
- Provides 2200 lumens
- Chipset provides 5000K day light with a high color rating of 82
- RoHS Certified
- Shatterproof coated for use in food service area

#### MODEL NUMBER: LT815850BDEC

#### ORDER CODE: 11125

## DLC: Pending

#### PACK SIZE: 25



#### **DIMENSIONS:**

- Diameter: 1 inch
- Nominal Length: 48 inches

