

LED 2x4 Panel

LED Flat Panel 2x4 120-347V
50 Watt 5000 Lumens 5000K



Product Description



The 2x4 LED Panel light is constructed using an extruded aluminum frame with a high quality PMMA light distribution panel combined with an attractive acrylic lens that achieves a wide light distribution pattern. The use of PMMA assures that the LED light panel will not yellow over time. EarthTronics guarantees the lens against yellowing for the life of product.

This 2x4 panel features 120-347V dual voltage operation and is equipped standard with a 0 - 10 Volt continuous dimming driver that works with any standard 0 - 10 Volt control/dimmer. The 5000K light and high 82+CRI provides a daylight solution.

These Panel lights are ideal for use in offices, schools, healthcare, and many other commercial applications. IC Rated.

LED Panels feature

- Solid construction frame is suitable for pendant mounting.
- Earthquake clips are standard on each panel light.
- 120-347VAC operation with 0-10V dimming is standard.
- PMMA light distribution panel evenly distributes the light across the face of the panel and does not yellow over time.
- Acrylic lens provides an attractive appearance and wide light distribution.
- Emergency back-up driver system is available, contact EarthTronics for details.



Electrical	
Watt	50
Voltage	120-347V
Min. Start Temperature	-40°C
Max. Operating Temperature	40°C
Driver Type	Class2
Driver Output	27-42V Direct Current
Dimming	0 – 10 Volt

Light	
Initial Lumens	5000
Lumens per Watt	100
Color Temperature	5000K
Color Rendering (CRI)	80
Beam Angle	150°

Agency Approvals	
DLC	Yes
FCC / ETL	Yes
IC Rated	Yes

Product Details	
Housing Material	Extruded Aluminum
Lens Material	Acrylic
Warranty	5 years, 10 year limited
Rated Life	50,000 hours

Order Code: 11151

UPC: 840791111512

DLC Product ID: PLOH7V412K5B

Model: LFP2X45050D5

Accessories (Ordered Separately)

- Surface Mount Kits 2x4 – Order Code: 10460
- Wire Hanger Kit 2x4 - Order Code: 10466