

# LED UFO Highbay

UFO Highbay LED 4000K  
26400 Lumens 200 Watt



| Electrical                      |                          |
|---------------------------------|--------------------------|
| Watt                            | 200                      |
| Voltage                         | 347-480V                 |
| Power Factor                    | >0.9                     |
| Total Harmonic Distortion (THD) | ≤20%                     |
| Min. Start Temperature          | -20°C (-4°F)             |
| Max. Operating Temperature      | 50°C (122°F)             |
| Light                           |                          |
| Initial Lumens                  | 26400                    |
| Lumens per Watt                 | 132                      |
| Color Temperature               | 4000K                    |
| Color Rendering (CRI)           | 80+                      |
| Agency Approvals                |                          |
| DLC Premium                     | Yes                      |
| UL                              | Yes                      |
| RoHS                            | Yes                      |
| Product Details                 |                          |
| Lens                            | Clear Acrylic, Impact    |
| Warranty                        | 5 year (10 year limited) |
| Rated Life                      | 50,000 hours             |
| Diameter                        | 15.28"                   |

## PRODUCT DESCRIPTION

EarthTronics Highbay LED delivers excellent energy savings when replacing up to 400 watt HID fixtures. This 200 watt fixture has a 15.28" diameter design and produces 26,400 lumens which is suitable for 15-35' mounting heights. It features 4000K color temperature with a high 80+ CRI providing excellent visual acuity for accuracy when working in manufacturing and warehousing applications. The pure 1060 aluminum housing provides excellent heat dissipation providing high lumen maintenance over its service life. IP65 rated for exposed applications. 0-10V dimming standard and compatible with several controls.

## PRODUCT FEATURES

- 347-480VAC 50-60Hz
- DLC Premium operating at 132 lumens per watt
- 120° beam angle with use of standard polycarbonate lens
- Features Seoul LED chip
- 4kV surge protector built in
- Powered by Sosen driver
- 0-10V dimming (pre-wired)
- Ships with a standard polycarbonate lens
- Ships with standard 6' 18/3 SJT whip and mounting ring
- IP65 wet location rated
- Replaces up to:
  - 400 watt MH systems
  - 6-lamp T5HO systems, 8 lamp T8

## APPLICATIONS

- Warehouse
- Manufacturing Facility
- Cafeteria
- Auditorium
- Gymnasium

**ORDER CODE:** 10914

**MODEL NUMBER:** HBU2700040BK4

**DLC PRODUCT ID:** PLQXEHK3IZC6

**UPC:** 840791109144

**CAUTION :** If the fixture is to be removed or replaced, please ensure that the electricity is switched off and that the fitting is cool before touching it.

