Panel

LED 5.5 inch Architectural Panel Light 11 Watt 700 Lumens 4000K





Electrical	
Watt	11
Voltage	120
Frequency	60Hz
Power Factor	0.9
Min. Start Temperature	-40°C
Max. Operating Temperature	40°C
Light	
Initial Lumens	700
Lumens per Watt	64
Color Temperature	4000K
Color Rendering (CRI)	90
Beam Angle	100°
Agency Approvals	
Energy Star	Yes
FCC	Yes
ETL	Yes
Product Details	
Lens Material	Acrylic
Warranty	5 years (based on 6 hours/ day)
Rated Life	50,000 hours

Product Description

The 5.5" LED Panel light is constructed using attractive impact resistant acrylic lens that helps achieve a wide light distribution pattern. These Panel lights are ideal for use in residential, offices, schools, healthcare, and many other commercial applications. Designed for easy installation in retrofit or new construction projects. Energy Star rated.

This 5.5 watt panel light produces 700 lumens of 4000K high >90 CRI light quality. Operates on 120VAC 60Hz and is compatible with standard incandescent dimmer controls providing a 100% to 5% dimming range. Easily installs on 4" j-boxes. Also can be used as a retrofit for 4" downlight recessed fixtures with an available accessory kit. Not for use in outdoor locations.

Product Features

- Easily installs on 4" j-box
- 700 lumens, 4000K
- Exceptional color rendering CRI >90
- Smooth edgelit LED technology
- · Wet location, perfect for shower applications
- 4" recessed can accessory kit available
- · Not for use in outdoor locations
- · Wet location rated
- 50,000 hour rated life
- Energy Star rated

Order Code: MP02700405WH2

Model Number: MP02700405

UPC: 840791109243

Dia. X MOL: 5.59" x 1.65"

Weight: 0.62 lb





