

LED Plug In

9 Watt 4000K 2-Pin LPD9M/GX23/840 LED Plug In



PRODUCT DESCRIPTION

EarthTronics 9 watt LED, LPD9M/GX23/840 easily replaces 13 watt GX23-2 base compact fluorescent lamps and provides 33% energy savings. It is physically the same form factor as the CFQ13W/GX23 that it replaces. This 2-pin lamp produces 800 lumens and works directly on magnetic ballast. No rewiring necessary. Instant on, no warm up time and a long service life make this lamp an easy choice in many applications. Available colors include 3000K, 4000K and 5000K and the CRI rating is >80. The unique design illuminates nearly identically to the bulb it replaces and can be used in any rotation or orientation in open fixtures. The 25,000 hour rated life provides 3 times the service life of a typical compact fluorescent lamp. For use only on single lamp ballast. Not for use in enclosed fixtures.

PRODUCT FEATURES

- Same form factor as the PL lamp it replaces.
- Light distribution pattern is nearly identical to PL lamps.
- Works directly on magnetic ballasts for easy “plug & play” installation.
- LED provides instant on and full brightness – no waiting.
- Also available in 3000K and 5000K color temperatures.

Applications:

- Recessed downlights
- Wall sconce
- Vanity fixtures
- Surface mount ceiling & wall fixtures
- Outdoor post lamps
- Outdoor flood lights

Ordering Code:

- 10175
- 12 pack inner, 48 pack master

Model:


- LPD9M/GX23/840

Replaces:

- GE F13DBX/840/ECO
- Philips PL-C13W/840/USA/Alto
- Sylvania CF13DD/840
- Any PL lamp utilizing the GX23-2 base, 2-pin

Cautions:

- Not for use on 2 lamp ballast. Intended for 1 lamp per ballast.
- Not for use in enclosed fixtures.
- This 2-pin LED lamp is intended for use on Magnetic ballast.
- Not for use with dimmer controls.
- Not for use with emergency lighting.



GX23-2 base, 2-pin

Electrical	
Watt	9 watt
Power Factor	> 0.50
Ballast required	Magnetic
Base Type	GX23-2, 2-Pin
Min. Start Temp	0° F
Max. Operating Temp	120° F
Light	
Initial Lumens	800
Lumens per Watt	88 lpw
Color Temperature	4000K
Color Rendering (CRI)	82
Beam Angle	Full radial
Agency Approvals	
UL	Yes
RoHS	Yes
FCC	Yes
Product Details	
Warranty	10 years, 6 hours per day
Mercury Content	No Hg
Overall Length	6.6"