

LED BRT

Adjustable LED Downlight Trim Bulb 4" – 8.5 Watt LED 3000K



PRODUCT DESCRIPTION

EarthTronics Adjustable LED Trim Kit provides a simple and quick way to upgrade recessed downlight fixtures. It's as simple as screwing in a light bulb. The screw base neck is depth adjustable to reach the fixture socket to make the power connection and fit against the ceiling. In addition the trim ring is replaceable and can be exchanged with other optional color and finish trim rings. This LED trim kit provides 3000K pleasing bright white with exceptional 90CRI. Perfect for residential use in kitchens and family rooms. Commercial applications include hospitality, long term care facilities and any downlight fixture that would benefit from an upgrade. Easily replace up to 65 watt BR30 flood lamps with this dimmable 8.5 watt LED trim kit for 80% energy savings. Features a long 25,000 hour rated life.

PRODUCT FEATURES

- 650 lumens bright white 3000K with exceptional 90 CRI color rendering
- 90° beam angle provides a full flood light
- Smooth dimming to less than 5%

PRODUCT APPLICATIONS



INSTALLATION



WORLD-CLASS LED CHIP

COLORED TRIM

HEATSINK

FLEXIBLE LAMP NECK

Screw the lamp neck counterclockwise to adjust the length

STANDARD MEDIUM BASE Easy for installation

MODEL NUMBER: LRTA4830D
ORDER CODE: 10597

| Order Code | Pack Size | Individual UPC | Master Park UPC | Qty |
|---|-----------|--------------------|----------------------|-----|
| 10597 | 1 | 840791105979 | 84079110597900 | 10 |
| Dimensions (inches - Length x Width x Height) | | | | |
| 10597 | 1 | 6.29 x 4.30 x 6.28 | 13.27 x 22.64 x 7.36 | 10 |
| Weight (lbs) | | | | |
| 10597 | 1 | .49 | 5.02 | 10 |

| Electrical | |
|--------------------------|----------------------|
| Watt | 8.5 |
| Power Factor | > 0.90 |
| Voltage | 120 volt |
| Frequency | 60hz |
| Min. Start Temp | -4F |
| Max. Operating Temp | 104F |
| Base Type | E26 Medium |
| Light | |
| Initial Lumens | 650 |
| Lumens per Watt | 78 |
| Color Temperature | 3000K |
| Color Rendering (CRI) | 90 |
| Beam Angle | 90° |
| Agency Approvals | |
| UL | Yes |
| Rated Life | 25,000 hr rated |
| RoHS | Yes |
| FCC | Yes |
| Product Details | |
| Warranty | 5 years 6 hrs/day |
| Trim Diameter | 5.25" |
| Fixture Nominal Diameter | 3.94" to 4.29" |