



EarthTronics® Linear LED Highbay

New Compact, Energy-Efficient LED Highbay Fixture with increased energy savings compared to linear fluorescent and HID fixtures.

Key Features

- + Versatile LED replacement to T8 or T5 fluorescent highbay fixtures
- + DLC® Premium operating at 130+ lumens per watt
- + Ships complete with 6-foot 300V FT2 18/3 SJT, hangers and chain for easy installation
- + 0-10V dimming and 100-277V driver is standard
- + Rated for damp location
- + Up to 42,000 lumen models available
- + Standard with high 84 CRI in both 4000K and 5000K
- + 90+CRI for color critical applications available by special order
- + PIR motion and PIR multifunction sensors available



DESCRIPTION

EarthTronics LED Highbay fixture enables exceptional energy savings compared to similar linear fluorescent and HID fixtures.

This LED product also provides excellent visual acuity for accuracy in manufacturing and warehousing applications. EarthTronics' LED Highbay fixtures are available in a 2' linear fixture and a 4' linear fixture for high lumen applications up to 42,000 lumens. It is suitable for 15' to 45' mounting heights.

The fixture offers 4000K and 5000K color temperature with a high 80+ CRI for highbay applications. Its durable white-finish metal body provides excellent heat dissipation. High quality Seoul LED chips provide for excellent lumen maintenance. L95 is at 50,000 hours and L80 at 120,000 hours (68°C).

EarthTronics' LED Highbay fixtures operate on standard 120-277 VAC and it is also available in 347-480 volts. It has an operating temperature range of -4°F to 122°F.

APPLICATIONS

- + Manufacturing Facility
- + Cafeteria
- + Auditorium
- + Gymnasium
- + Warehouses

SPECIFICATIONS & CERTIFICATIONS



OPTIONS AVAILABLE

- + Emergency Back-up power supply is available
- + PIR occupancy sensor 120-347V, 480V
- + PIR with Daylight Harvesting on 120-277V systems
- + Wire Guards
- + Pendant mounting kit
- + Surface mounting kit

DLC® PREMIUM PERFORMANCE

EarthTronics selected world-class LED chips and high quality drivers engineered to perform at an efficiency level necessary to meet and exceed DLC premium standards.

OPERATION

Standard linear highbay is 120–277 VAC and 347–480 VAC is available. All models include 0-10V dimming. Sensors are available with occupancy, step dimming, and daylight harvesting capabilities.

PRODUCT OFFERING

Lumens	Wattage	Color Temp
13775	105	5000K
14410	110	4000K, 5000K
21222	162	4000K, 5000K
28165	215	5000K
29213	223	4000K, 5000K,
41920	321	4000K, 5000K

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: [Rebate Finder - Highbay Linear](#)

www.earthtronics.com/rebate-finder/catalog/