

Project	
Date	
Prepared By	
Model #	WPT40CCTBK5

Specifications

ELECTRICAL

Watts: 40

Voltage: 100-347VAC

Power Factor: 0.9

Operating Temp. Range:
-40°F to 131°F

LIGHT

Initial Lumens: 5500

Lumens per Watt: 138

Color Temperature:
3000K, 4000K, 5000K

CRI: 82

AGENCY APPROVALS

DLC® Premium: Yes

UL/cUL: Yes

RoHS: Yes

PRODUCT DETAILS

Lens: Glass

Warranty: 5 years

Fixture

Rated Life: 50,000 hours

Weight: 9.16 lbs

Dimensions:

15.36" L x 11.42" W x 12.2" D

LED Wall Pack - Color Selectable

5500 Lumens, 40 Watt, CCT Selectable, 100-347V



ORDER CODE:
11556

MODEL NUMBER:
WPT40CCTBK5

DLC PRODUCT ID:
PL0A6P47QFII

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

EarthTronics Traditional LED Wall Packs features three color selectable operations. Switch between 3000K, 4000K and 5000K easily at the time installation. The LED Traditional Style Wall Pack uses Seoul LED chips and drivers to deliver a quality, energy saving lighting solution. The color selectable temperatures offer building managers the opportunity to match existing HID lamps to reduce the blue light spectrum often associated with higher color temperatures. Each of the EarthTronics Wall Packs accepts 100-347 volt AC power supply. The wall packs provide more than 138 lumens per watt and a high 80+ CRI for improved visual acuity and efficient performance. The design is built to withstand all climates and allows for an extreme temperature range, even operating down to -40 degrees F°, and is IP65 approved for outdoor wet applications. With rated life of 50,000 hours, this wall pack series is designed for easy installation, directly fitting onto existing electrical boxes, making it the contractor's choice when replacing older high-pressure sodium and metal halide wall packs. DLC® Premium listed product.

PRODUCT FEATURES

- + DLC® Premium
- + 3 color of light selection assures you of the proper light color every installation
- + Select from 3000K, 4000K and 5000K
- + Easily replace existing wall packs for wide area illumination
- + IP65 rated for outdoor use
- + 50,000 hour rated life
- + Tempered and impact resistant clear prismatic borosilicate glass lens
- + Die cast aluminum housing provides long life in commercial installations
- + 120° light pattern provides for wide flood distribution
- + Night Sky Compliant
- + Photocell build in

APPLICATIONS

- + Commercial Building
- + Industrial
- + Municipal Facilities

Please consult installation instructions for proper application and use of this fixture.
*Rebate availability access it here: www.earthtronics.com/rebate-finder

PRODUCT DIMENSIONS



PACKAGE DETAILS

Dimensions:

15.75" Length x 11.81" Width x 12.60" Depth

Weight: 10.78 LBS

UPC: 84079111115565

PRODUCT VIEWS



OPTIONAL ACCESSORIES



Traditional Wall Pack
Backup Driver

Order Code: 11468

Easily access our DLC qualified products with rebates in your area.

[ACCESS IT HERE: Traditional LED Wall Pack](#)

www.earthtronics.com/rebate-finder/catalog/

