

| Project     |             |
|-------------|-------------|
| Date        |             |
| Prepared By |             |
| Model #     | LT834850BDE |

# Specifications

#### **ELECTRICAL**

Watts:

34 watt lamp

Voltage:

120-277V 50/60Hz

Power Factor: >0.9

Operating Temp. Range:

-20°C to 45°C

Base Type: FA8 1Pin

#### **LIGHT**

Initial Lumens: 4400 Lumens per Watt: 129

Color Temperature: 5000K

**CRI:** >82

#### **AGENCY APPROVALS**

UL/FCC: Yes RoHS: Yes

#### PRODUCT DETAILS

Warranty: 10 years

**Fixture** 

Rated Life: 50,000 hours

Weight: 0.41lbs

Dimensions: 1" Diameter 96" Length



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

# LED Linear Tube 96"

Type B, 4400 Lumens, 34 Watt, 5000K



MODEL NUMBER: LT834850BDE LENGTH:

**ORDER CODE:** 

96 Inch Type B

11359



### PRODUCT DESCRIPTION

Easily replace T12 and T8 96" fluorescent lamps and save up to 65%\* in energy costs. The EarthTronics 96" TLED provides 4400 lumens and consumes only 34 watts. The lamp CCT is 5000K and provides 82CRI for improved visual acuity and color clarity when compared to the fluorescent lamps being replaced. The construction is glass and the light distribution is 300° which makes the lamp an easy answer when retrofitting simple strip fixtures or more decorative pendant fixtures. This Type B direct wire lamp is easily installed with simple rewiring directly to 120VAC or 277VAC power supply. Follow the instructions provided to wire the load (black wire) to one end of the lamp and the neutral (white wire) to the other end. There is no need to replace lamp holder sockets. The EarthTronics 96" TLED is a perfect for use in schools, institutions, warehouses, retail and other commercial applications where energy savings is required. 50,000 hour rated life. Fa8 lamp base type. Operates on 120 – 277VAC.

\*when replacing a 72 watt T12 fluorescent

#### **PRODUCT FEATURES**

- + Easily retrofit T8, 8 foot tubes
- +DLC® Technical Requirements 5.0
- + Direct wire eliminates the need for electronics ballast or drivers
- + 5000K daylight with a high color rendering rating of 82
- + 120-277VAC 50/60Hz
- + Provides 4400 lumens
- + Conforms to UL Standard 1993 and 1598C. Certified to CSA Standard C22.2 No. 1993 & C22.2 No. 250.1

Please consult installation instructions for proper application and use of this fixture.

\*Rebate availability access it here: www.earthtronics.com/rebate-finder



Type B, 4400 Lumens, 34 Watt, 5000K

#### PACKAGE DETAILS

#### MASTER CARTON

Master Carton Oty: 10

Dimensions: 97.7" Length x 7.7" Width x 5.88" Height

Weight: 11.91 lbs


UPC: 84079111359200

#### LAMP BASETYPE

## OPTIONAL ACCESSORIES - (Sold separately)



FA8 1Pin



External Emergency Backup Kit

Order Code: 11405

Dimensions:

23.97" Length x 23.97" Width x 2" Depth

Weight: 6.75 LBS UPC: 84079112526

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: Rebate Finder - Linear Tube

www.earthtronics.com/rebate-finder/catalog/





