

Project	
Date	
Prepared By	
Model #	LT815835AG6S

## Specifications

### ELECTRICAL

**Watts:**

15 watt lamp

**Voltage:**

For use with electronic ballast

**Power Factor:** >0.9

**Operating Temp. Range:**

-20°C to 45°C

### LIGHT

**Initial Lumens:** 2100

**Lumens per Watt:** 147

**Color Temperature:**

3500K

**CRI:** >82

### AGENCY APPROVALS

**DLC® Standard:** Yes

**UL/FCC:** Yes

**RoHS:** Yes

### PRODUCT DETAILS

**Lens:** Acrylic

**Warranty:** 10 years

**Fixture**

**Rated Life:** 50,000 hours

**Dimensions:**

1" Diameter

48" Length



Muskegon, Michigan 49441

T: 231.332.1188 | F: 231.726.5029

TOLL FREE: 866.632.7840

www.earthtronics.com

# LED Linear Tube

2100 Lumens, 15 Watt, 3500K



### ORDER CODE:

11390

### MODEL NUMBER:

LT815835AG6S

### DLC® PRODUCT ID:

PLCXZHB1SE6N

### UPC:

840791113905

## PRODUCT DESCRIPTION

15 watt EarthBulb LED linear tube is available in 3500K with 300 degree beam angle. Great light output and perfect for replacement of T8 fluorescent tubes. This linear tube provides 2100 lumens and has a CRI of 82. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. Simply "plug and play" on Instant Start electronic fluorescent ballasts. Compatible with instant start, program start and rapid start T8 electronic ballast. Also compatible with fluorescent emergency ballasts. DLC® listed product. Download compatibility list [here](#).

## PRODUCT FEATURES

- + 15 watt lamp energy use
- + "Plug and play" on T8 systems utilizing Instant Start, program start and rapid start electronic ballast
- + Easily retrofit T8, 4 foot tubes
- + Provides 2100 lumens
- + Chipset provides 3500K cool white light with a high color rendering rating of 82
- + No Mercury, RoHS Certified

Please consult installation instructions for proper application and use of this lamp.

\*Rebate availability access it here: [www.earthtronics.com/rebate-finder](http://www.earthtronics.com/rebate-finder)

Rev. 4.13.20 | ET11390