

Project	
Date	
Prepared By	
Model No.	LA191150DESEF

Specifications

ELECTRICAL

Watts: 11 Voltage: 120 volt, 60Hz

Power Factor: >0.9

Base Type: E26 Medium

Operation: Dimmable

Operating Temp. Range: -4°F to 104°F

LIGHT

Initial Lumens: 1100 Lumens per Watt: 100 Color Temperature: 5000K CRI: 84

AGENCY APPROVALS

UL/FCC: Yes RoHs: Yes Energy Star: Yes

PRODUCT DETAILS

Warranty: 3 years Rated Life: 15,000 hrs. Dimensions: Length: 4.64" Diameter: 2.36"



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

LED A19 1100 Lumen, 11 Watt, 5000K



ORDER CODE: 11237

MODEL NUMBER: LA191150DESEF

OPERATION: Dimmable

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

11 watt A19 Omni-directional EarthBulb LED provides 1100 lumens and replaces 75 watt incandescent directional bulbs for over 80% energy savings. 5000K color of light is standard. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. Suitable for outdoor use, damp location, when installed in fixtures and not directly exposed to weather. Energy Star rated for use in enclosed fixtures.

PRODUCT FEATURES

- + This A bulb is Energy Star rated and provides 1100 lumens, capable of dimming to less than 10%
- + Suitable for damp locations
- + 5000K daylight with a high color rendering rating of 84
- + May be used in enclosed fixtures
- + Omni directional beam angle provides full radial illumination + Vanities

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Carton Oty: 1 Dimensions: 2.48" L × 2.48" W × 4.72" D Weight: 0.39 LBS UPC: 840791112373

INNER CARTON

Inner Carton Qty: 12 Dimensions: 10.47" L x 7.91" W x 5.39" D Weight: 3.02 LBS UPC: 00840791112373



MASTER CARTON

APPLICATIONS + General Purpose

+ Table Lamps

+ Floor Lamps

+ Wall Sconce

+ Ceiling Fixtures

Master Carton Oty: 48 Dimensions: 21.73" L x 16.61" W x 6.73" D Weight: 12.89 LBS UPC: 84079111237300