

Project	
Date	
Prepared By	
Model #	DL4WSCCTWH1

Specifications

ELECTRICAL

Watts: 5, 7, or 12
Voltage: 120-277VAC
Dimming: 0-10V
Power Factor: 0.98
Operating Temp.:
 -40°F - 135°F

LIGHT

Lumens:
 500, 700 or 1000
Color Temperature:
 3000K, 3500K, 4000K
CRI: 94

AGENCY APPROVALS

UL / cUL: Yes
Wet Location: Yes
California: JA8, Title 24
Ratings: Type IC


MATERIALS

Driver Housing:
 Cast Aluminum
Fixture Body:
 Spun Aluminum
Lens:
 Optical polycarbonate

RATED LIFE

Warranty: 5 years
Life: 50,000 hours L80

4" Commercial Downlight LED Fixture Color and Wattage Selectable



ORDER CODE:
 11725

MODEL NUMBER:
 DL4WSCCTWH1

COLOR SELECTABLE:
 3000K, 3500K, 4000K

LUMEN LEVEL:
 500 lumens - 5 watts
 700 lumens - 7 watts
 1000 lumens - 12 watts

PRODUCT DESCRIPTION

The EarthTronics LED architectural grade downlight fixture provides the flexibility to insure the correct light level and color temperature desired in different applications. Select from 3000K, 3500K or 4000K color temperatures as well as 500, 700 or 1000 lumen levels with a switch located on the driver housing. The fixture features a matte-white finish, frosted lens and a deep parabolic design which provides an ample cut-off angle. This 4" fixture can be used in new construction or in retrofit/renovation applications. The durable corrosion resistant stainless-steel spring clips accommodate up to 2" thick ceilings. The driver operates on 120-277VAC and is complete with 0 – 10 volt dimming. The die-cast driver housing and high quality LED chips provide 50,000 hour rated life at L80. Five year warranty. Meets strict California JA8 standards and is Title 24 compliant. IC Rated for use in insulated ceiling applications and meets IECC air leakage requirements. Maybe be installed in wet locations such as soffit and covered walkway installations, out of direct weather.

PRODUCT FEATURES

- + Color selectable: 3000K, 3500K, 4000K
- + 90+ CRI enhanced color clarity
- + Easy Installation
- + 0-10 volt dimming, 120-277VAC
- + 50,000 hour rated life
- + Wet location rated
- + Replace 35 to 50 watt HID downlight cans
- + JA8, Title 24, IC Rated, meets IECC requirements
- + Durable Aluminum Housing with spring-loaded retention clips

APPLICATIONS:

- + Commercial buildings
- + Mezzanine level downlights

Please consult installation instructions for proper application and use of this fixture.
 *Rebate availability access it here: www.earthtronics.com/rebate-finder