

Project	
Date	
Prepared By	
Model No.	LP2530D8

Specifications

ELECTRICAL

Watts: 5

Input Current: 85 (mA)
Power Factor: 0.8
Voltage: 120 volt, 60Hz

Base Type: E26 Medium Operation: Dimmable

Operating Temp. Range:

-4°F to 104°F

LIGHT

Initial Lumens: 520 Lumens per Watt: 74 Color Temperature: 3000K

CRI: 80+

Beam Angle: 40°

AGENCY APPROVALS

UL/FCC : Yes Energy Star: Yes

RoHs: Yes

PRODUCT DETAILS

Warranty: 10 years
Rated Life: 15.000 hrs.

Dimensions: Length: 2.5" Diameter: 3.35"



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

LED PAR20

520 Lumen, 5 Watt, 3000K



ORDER CODE:

11577

MODEL NUMBER:

LP2530D8

OPERATION:

Dimmable

ENERGY STAR ID:

2396736

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

5 watt PAR20 EarthBulb LED floodlight replaces 50 watt incandescent floodlights for over 80% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. PAR20 can be used indoor or outdoor.

PRODUCT FEATURES

- + This PAR20 provides 520 lumens
- + Dimming to less than 10%
- + Energy Star rated product
- + Suitable for damp locations
- + 3000K white light with a high color rendering rating 80+
- + 40° beam angle provides full radial illumination

APPLICATIONS

- + Recessed Can fixtures
- + Track Lighting
- + Display Lighting
- + Corridor Lighting
- + Large hanging pendants

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Carton Qty: 1 Dimensions:

2.50" L x 2.50" L x 3.42" H

Weight: 0.462 LBS UPC: 840791115770

INNER CARTON

Master Carton Oty: 12

Dimensions:

10.55" L x 7.96" W x 3.93" H

Weight: 1.83 LBS UPC: 84079111577000

MASTER CARTON

Master Carton Oty: 24

Dimensions:

10.9" L x 8.30" W x 8.50" H

Weight: 7.78S LBS UPC: 84079111577000







