

Project	
Date	
Prepared By	
Model #	LST4WSCCTD1

Specifications ELECTRICAL

Watts: 22, 28, 40

Voltage: 120-277VAC

Power Factor: 0.9

Operating Temp. Range: -20°C (-4°F) to 50°C (122°F)

LIGHT

Initial Lumens: 2860, 3640, 5200

Color Temperature: 3500K, 4000K, 5000K CRI: 80+

AGENCY APPROVALS

ULListed 1598: Suitable for dry and damp locations DLC® Listed: Yes

PRODUCT DETAILS

Lens: Frost Polycarbonate Warranty: 5 years

Fixture Rated Life: 50,000 hours Lumen Maintenance: L70 at 100,000 hrs (70°C) Weight: 5.40 LBS Dimensions: 48.82" L x 3.70" W x 3.78" D



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

LED Strip 48"

Color and Wattage Selectable



ORDER CODE: 11609

MODEL NUMBER: LST4WSCCTD1

COLOR SELECTABLE: 3500K, 4000K, 5000K

LUMEN LEVEL:

2860 lumens - 22 watts 3640 lumens - 28 watts 5200 lumens - 40 watts

DLC® PRODUCT ID: S-GQOH9Y

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

EarthTronics LED Strip fixture provides the flexibility to insure the correct light level and color temperature desired in different applications. Select from 3500K, 4000K or 5000K color temperatures as well as 2860, 3640 or 5200 lumen levels, this is easily done by the two DIP switch buttons integrated into the driver. This strip fixture is a standard 48" long. It features a high 80+ CRI providing an excellent light source for nearly any task. The fixture body is white painted durable steel with a polycarbonate lens. These strip fixtures feature 120-277V dual wattage operation. They are equipped standard with a 0 - 10 volt continuous dimming driver with a dimming range capability of 10% to 100%. DLC® listed product.

PRODUCT FEATURES

- + Color selectable: 3500K, 4000K or 5000K
- + Wattage selectable: 22, 28, 40
- + Standard 120-277V
- + Dimming range of 10% to 100%
- + UL 1598 suitable for dry and damp locations

APPLICATIONS

- + Manufacturing
- + Education
- + New Construction

- + DLC® Listed
- + L70 at 100,000 hours (70°C)
- + Factory preset to maximum wattage, 4000K
- + Microwave sensor available
- + 0-10V continuous dimming driver
- + Emergency back-up power supply available
 - + Low-Bay
 - + General Lighting

Please consult installation instructions for proper application and use of this fixture. *Rebate availability access it here: www.earthtronics.com/rebate-finder



LED Strip 48"

Color and Wattage Selectable

PACKAGE DETAILS


INDIVIDUAL PACKAGE

Individual Carton Qty: 1 Dimensions: 48.82" Length x 3.70" Width x 3.78" Depth Weight: 5.40 LBS UPC: 840791116098

MASTER CARTON

Master Carton Qty: 6 Dimensions: 49.41" Length x 11.73" Width x 8.23" Height Weight: 35.49 LBS UPC: 84079111609800

LIGHTING LAYOUT



Average Illuminance: 25 fc Number of Luminaires: 2 Workplane Height: 2.5 ft

OPTIONAL ACCESSORIES



Microwave Sensor 120/277V (stand-alone) Order Code: 11638



for multiple sensors.

*Note: 11683 - one remote control

Remote Control for Microwave Sensor* Order Code: 11683



Right Angle Connector Order Code: 11820

Row Connector Order Code: 11819 Aft Wirequard

4ft Wireguard Order Code: 11821



Emergency Back-up Driver & Battery Order Code: 11639

4ft Replacement Lens Order Code: 11737



Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: <u>Rebate Finder</u> www.earthtronics.com/rebate-finder/catalog/