

Project	
Date	
Prepared By	
Model #	CA50WSCCTBK1

## **Specifications**

#### **ELECTRICAL**

Watts: 30, 40, 50 Voltage: 120-277VAC Power Factor: >0.9 Operating Temp. Range: -40°F (-40°C) to 113°F (45°C)

#### **LIGHT**

Lumens: 3900, 5200 or 6500

Color Temperature: 3000K, 4000K or 5000K

CRI: 80+

#### **AGENCY APPROVALS**

**UL:Yes** 

**UL Wet Location Rated: Yes** 

DLC® Premium: Yes

#### PRODUCT DETAILS

Finish Color: Black Lense: Polycarbonate Warranty: 5 years

**Fixture** 

Rated Life: 50.000 hours Lumen Maintenance:

L70 at 54,000 (75°C)

Dimensions: 9"Lx9"W



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

# LED Canopy

Color and Wattage Selectable





**ORDER CODE:** 

11625

**MODEL NUMBER:** CA50WSCCTBK1

**COLOR SELECTABLE:** 3000K, 4000K, 5000K

#### LUMEN LEVEL:

3900 lumens - 30 watts 5200 lumens - 40 watts 6500 lumens - 50 watts

**DLC® PRODUCT ID:** PLD94FJ5VT21

**REBATE AVAILABILITY\*** 

#### PRODUCT DESCRIPTION

EarthTronics LED Canopy Fixture features a low profile design that provides the flexibility to insure the correct light level and color temperature desired in different applications. Select from 3000K, 4000K or 5000K color temperatures as well as 3900, 5200 or 6500 lumen levels, this is easily done by the dial switch located on the side of the product. It features a high 80+ CRI providing an excellent light source for nearly any task. The lens are sealed to and tested for IP65. These canopy fixtures feature 120-277V dual wattage operation. They are equipped standard with a 0 - 10 volt continuous dimming driver with a dimming range capability of 10% to 100%. This fixture is ideal for warehouses, offices, factories, hospitals and hotels. Photocell option is built in which helps improve security. DLC® listed product.

#### PRODUCT FEATURES

- + Select from 3000K, 4000K & 5000K
- + Wattage selectable: 30, 40, 50
- + Standard 120-277V
- + 0-10V continuous dimming driver
- + Photocell built in
- + Dimming range of 10% to 100%

- + Suitable for wet locations
- + Factory preset to maximum wattage, 5000K
- + Sealed to and tested for IP65
- + 4K surge protector
- + DLC® Technical Requirement 5.1

#### **APPLICATIONS**

+ Warehouses

+ Offices

- + Hotels
- + Hospitals
- + Factories + Parking Garage
- MOUNTING OPTIONS
- + Surface J-Box
- + Pendant Mount

Please consult installation instructions for proper application and use of this fixture.


<sup>\*</sup>Rebate availability access it here: www.earthtronics.com/rebate-finder




Color and Wattage Selectable

#### PRODUCT DETAILS

### PACKAGE DETAILS





#### INDIVIDUAL PACKAGE

Individual Carton Oty: 1

Dimensions:

10.23" L x 9.84"D x 3.74" W

Weight: 3.92 LBS

UPC: 840791116524

#### **MASTER CARTON**

Individual Carton Oty: 5

Dimensions:


11.02" L x 19.48" D x 10.63" W


Weight: 22.44 LBS

UPC: 84079111652400

#### COLOR AND WATTAGE SELECTABLE

**MOUNTING VARIATIONS** 












Surface Mount



**Pendant Mount** 

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: Rebate Finder - LED Canopy

www.earthtronics.com/rebate-finder/catalog/





