

Project	
Date	
Prepared By	
Model #	WPT4040BK5

## Specifications

### ELECTRICAL

Watts: 40

Voltage: 100-347VAC

Power Factor: >0.9

Operating Temp. Range:

-40°F to 131°F

### LIGHT

Initial Lumens: 5000

Lumens per Watt: 125

Color Temperature:

4000K

CRI: >80

### AGENCY APPROVALS

cUL: Yes

UL: Yes

RoHS: Yes

### PRODUCT DETAILS

Lens: Acrylic

Warranty: 5 years

Fixture

Rated Life: 50,000 hours

Dimensions:

10.3" L x 9.4" W x 9.8" H

### APPLICATIONS

+ Commercial Building

+ Industrial

+ Municipal Facilities

# Traditional Wall Pack

5000 Lumens, 40 Watt, 4000K, 100-347V



**ORDER CODE:**

11349

**MODEL NUMBER:**

WPT4040BK5

**UPC:**

840791113493

## PRODUCT DESCRIPTION

EarthTronics Traditional LED Wall Packs provide exterior, wide-flood area illumination for commercial, industrial and municipal facilities. Available in 40 watt with 4000K color of light, these fixtures provide 5000 lumens. The 40 watt models are built in a standard size 10.3" L x 9.4" W x 9.8" H aluminum alloy housing with a standard bolt pattern. The LED Traditional Style Wall Pack uses Lumiled LED chips and drivers to deliver a quality, energy saving lighting solution. The 4000K color temperature offers building managers the opportunity match existing HID lamps and to reduce the blue light spectrum often associated with higher color temperatures. Each of the EarthTronics Wall Packs accepts 100-347 volt AC power supply. The wall packs provide more than 125 lumens per watt and a high 80+ CRI for improved visual acuity and efficient performance. A dusk to dawn sensor is available and is easily added at the time of installation. The design is built to withstand all climates and allows for an extreme temperature range, even operating down to -40 degrees C°, and is IP65 approved for outdoor wet applications. With rated life of 50,000 hours, the WP5 wall pack series is designed for easy installation, directly fitting onto existing electrical boxes, making it the contractor's choice when replacing older high-pressure sodium and metal halide wall packs.

## PRODUCT FEATURES

- + Easily replace existing wall packs for wide area illumination
- + Tempered and impact resistant clear prismatic borosilicate glass lens
- + Die cast aluminum housing provides long life in commercial installations
- + 120° light pattern provides for wide flood distribution
- + IP65 rated for outdoor use
- + Photocell available and easily installed
- + 4000K CRI is standard



Side View



Back View