

Project	
Date	
Prepared By	
Model #	LT829840SEDE

# Specifications

# **ELECTRICAL**

Watts:

9 watt lamp

Voltage:

120-277V 50/60Hz

Power Factor: 0.90

Operating Temp. Range:

-20°C to 45°C

Base Type:

G13 Medium Bi-pin

# LIGHT

Initial Lumens: 1150 Lumens per Watt: 128 ColorTemperature: 4000K

**CRI:** 82

#### **AGENCY APPROVALS**

DLC®: Yes UL/FCC: Yes RoHS/ NSF: Yes

ETL: Yes

### PRODUCT DETAILS

Diffuser Type:

Internal coated glass tube

Warranty: 10 years

**Fixture** 

Rated Life: 50,000 hours

Dimensions:

1" Diameter 24" Length



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

# LED Linear Tube 24"

Type B, 1150 Lumens, 9 Watt, 4000K







# **ORDER CODE:**

11657

### **MODEL NUMBER:**

LT829840SEDE

# LENGTH:

24 Inch Type B

# **DLC PRODUCT ID:**

S-6814Z

**REBATE AVAILABILITY\*** 

# PRODUCT DESCRIPTION

9 watt EarthBulb direct wire LED linearT8 eliminates the ballast for maximum energy savings. Available in 4000K with 210 degree beam angle. Great light output and perfect for replacement of T8 fluorescent tubes. This linear tube provides 1150 lumens and has a CRI of 82. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. This lamp features a flexible design allowing for single-end or double-end operation on 120-277V. To install, simply remove the existing fluorescent ballast and direct wire the line voltage. Direct wire quickly, no lamp holder modifications necessary, just run the black (load) to the one end and white (neutral) to the other.

# PRODUCT FEATURES

- + Easily retrofit T8, 2 foot tubes
- + 120-277VAC 50/60Hz direct wire eliminates the need for electronics ballast or drivers
- +Direct wire without modifying lamp holders
- + 120-277VAC 50/60Hz
- + DLC® Technical Requirement 5.1
- +Continuous dimming down to 10%

- +Flexible design allows for single-end or double-end operation on 120-277V
- + Provides 1150 lumens
- + 4000K cool light with a high color rendering rating of 82
- +Conforms to UL Standard 1993 and 1598C. Certified to CSA Standard C22.2 No. 1993 & C22.2 No. 250.1
- +Emergency Driver available

Please consult installation instructions for proper application and use of this lamp.

\*Rebate availability access it here: www.earthtronics.com/rebate-finder



# LED Linear Tube 24"

Type B, 1150 Lumens, 9 Watt, 4000K

# PACKAGE DETAILS

#### INDIVIDUAL PACKAGE

Individual Carton Oty: 1

Dimensions: 24" Length x 1.2" Width x 1.2" Height

Weight: .29 lbs UPC: 840791116579

### MASTER CARTON

Master Carton Oty: 25

Dimensions: 25.2" Length x 5.9" Width x 5.9" Height


Weight: 8.22 lbs


UPC: 84079111657900

#### LAMP BASETYPE












# OPTIONAL ACCESSORIES - (Sold separately)



External Emergency Backup Kit

Order Code: 11405

Dimensions:

23.97" Length x 23.97" Width x 2" Depth

Weight: 6.75 LBS UPC: 84079112526

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: Rebate Finder – Linear Tube www.earthtronics.com/rebate-finder/catalog/





