

Project	
Date	
Prepared By	
Model #	AL300WSCCTBK5

LED Area Light

Color & Wattage Selectable 120/277VAC, 347VAC

ELECTRICAL

Watts: 300

Voltage: 120/277VAC, 347VAC Power Factor: 0.942 **THD:** 15.1%

Specifications

OperatingTemp. Range:

-40°C (-4°F) to 45°C (113°F)

Dimming: 0-10VDC Dim Capability & Range: Continuous down to 10%

LIGHT

Initial Lumens: 39000

Lumens per Watt: 130

Color Temperature: 3000K, 4000K, 5000K **CRI:** 73

AGENCY APPROVALS

UL/cUL: Yes **RoHS:** Yes IP65: Yes **DLC® Premium: Yes**

PRODUCT DETAILS

Housing: Die-cast aluminum alloy Warranty: 5 years Weight: 10.75 LBS



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com



PRODUCT DESCRIPTION

EarthTronics color and wattage selectable LED Area Lights low profile design that provides the flexibility to insure the correct light level and color temperature desired in different applications. Select from 3000K, 4000K or 5000K color temperatures as well as 26000, 31200 or 39000 lumen levels. LED Area Lights are ideal for exterior illumination for commercial, industrial, and municipal facilities. The durable die cast aluminum housing is powder coated to maintain the fixture appearance for several years. The area light provides more than 130 lumens per watt efficient performance. A dusk to dawn sensor is available and is easily added at the time of installation. The design is built to withstand all climates and allows for an extreme temperature range, even operating down to -40 degrees C°, and is IP65 wet location rated. The unique changeable mount system includes the following options: slip fitter with adjustable angle, straight mounts for poles and wall applications and a trunnion (yoke) mount. DLC® Premium listed.

PRODUCT FEATURES

- + Color Selectable: 3000K, 4000K, 5000K
- Lumen Selectable: 26000, 31200, or +39000
- + Provides more than 130 lumens per watt + DLC® 5.1 Technical Requirement
- Die-cast aluminum alloy housing provides + Compatible with EarthConnect, long life in commercial installations
- Standard 6KV surge protector included +(10KV optional upgrade available)
- + Driver standard with 0-10V dimming (prewired)

APPLICATIONS

- + Parking Lots + Campuses
- + Area Lighting + Grocery Store
- + Walkways + Commercial

- + Corrosion resistant finish & screws
- + UV resistant powder coat finish
- + IP65 wet location rated
- Networked Lighting Controls


Please consult installation instructions for proper application and use of this fixture. *Rebate availability access it here: www.earthtronics.com/rebate-finder



EarthTronics. LED Area Light

Color and Wattage Selectable 120/277V, 347V


PRODUCT DIMENSIONS



PACKAGE DETAILS

Individual Package: 1 Fixture Dimensions: 24.92"L x 15.28"W x 5.04"H Weight: 13.0 LBS UPC: 840791117668

Note: Mounting system ordered separately



Easily access our DLC qualified products with rebates in your area. ACCESS IT HERE: <u>Rebate Finder - LED Area Light</u>

www.earthtronics.com/rebate-finder/catalog/



EarthTronics, Inc. | Norton Shores, MI 49441 | www.earthtronics.com | Email: contact@earthtronics.com Toll Free: 866.632.7840

Rev. 10.30.2023 | ET11766