

Project	
Date	
Prepared By	
Model #	HBLWS185CCTWH1

### **Specifications**

#### **ELECTRICAL**

Watts: 135, 155, 185 Voltage: 120-277VAC Power Factor: >0.9

**THD**: ≤10%

Operating Temp. Range: -20°C (-4°F) to 50°C (122°F)

#### LIGHT

Initial Lumens: 27750 Lumens per Watt: 150 Color Temperature:

4000K, 5000K

**CRI:** 80

Dimming: 0-10V Dimmable: Yes

#### **AGENCY APPROVALS**

**UL:** Yes RoHS: Yes

#### PRODUCT DETAILS

Housing: Steel

Lens: PMMA optical glare-control lens

Warranty: 5 years

**Fixture** 

Rated Life: 50.000 hours

Lumen Maintenance: L70

at 100,000 hrs Weight: 5.5 LBS

**Dimensions:** 

22.8"L x 10.2"W x 1.8"D **Earth**Tronics.

Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

## Linear LED Highbay

Color & Wattage Selectable





11856

#### MODEL NUMBER:

HBLWS185CCTWH1

#### **LUMEN LEVELS:**

27750 lumens - 185 watts 23250 lumens - 155 watts 20250 lumens - 135 watts















#### PRODUCT DESCRIPTION

EarthTronics LED Linear High Bay features two color selectable operations and wattage selectable options of 185, 155 or 135 watt. Switch between 4000K and 5000K easily at the time installation. EarthTronics LED High Bay offers a small, lightweight design that delivers excellent energy savings without sacrificing performance. This wattage selectable LED High Bay has a 1.9ft design and provides 20250 up to 27750 lumens. It also It features a durable steel housing and with a high 80+ CRI providing excellent visual acuity for accuracy when working in manufacturing and warehousing applications.

#### PRODUCT FEATURES

- + Lightweight, compact design
- + 120-277VAC
- + Operating at 150 lumens per watt
- + 6kV ANSI surge protection standard
- + Integral LED lens is constructed from PMMA and provides even illumination
- + Durable steel housing
- + Up to 50°C true ambient temperature

- + Driver standard with 0-10V dimming (prewired)
- + Suitable for damp locations
- + Hanging hardware included V-Hooks &
- + Emergency back-up driver available
- + Compatible with EarthConnect® Network Lighting Controls
- + 6ft 18/3 SJT cord sold separately (see available options)

#### **APPLICATIONS**

- + Manufacturing Facility
- + Warehouse + Cafeteria
- + Auditorium
- + Gymnasium

Please consult installation instructions for proper application and use of this fixture.


\*Rebate availability access it here: www.earthtronics.com/rebate-finder




# EarthTronics. LED Linear Highbay

Color & Watttage Selectable

#### PRODUCT DIMENSIONS




LIGHTING LAYOUT




Average Illuminance: 30 fc Number of Luminaires: 3 Workplane Height: 2.5 ft

#### **OPTIONAL ACCESSORIES**



Pendant Hanger Order Code: 11711



Surface Mount Order Code: 11710




Wire Guard Order Code: 11713



12VDC Microwave Sensor
Order Code: 11778

Note: One remote control (11779) for multiple microwave sensors.



External Emergency Back up Kit (30W) Order Code: 11617

#### 6ft 18/3 SJT cord available (sold separately)

Order Code: 11836 6ft 18/3 SJTOOW 300V Cord - White (cord only)

Order Code: 11837 6ft Cord (18/3 SJT White) with 5-15P 120V 15AMP Plug

Straight Blade Plug - Black

Order Code: 11838 6ft Cord (18/3 SJT White) with NEMA L7-15P 277V 15AMP

Twist Lock Plug - Black

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: Rebate Finder - Linear LED Highbay

www.earthtronics.com/rebate-finder/catalog/



