

DesignLights Consortium



Model Number	LT832850BDE
Classification	Standard
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported Input Wattage	32 W
Reported Light Output	4400 lm
Reported CRI (Ra)	82
Product ID	PLQJRKTUQJM
DLC Family Code	EMWAHX
Listing Status	Listed
Date Qualified	2021-10-08
Reported CCT	5000 K

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLQJRKTUQJM
Manufacturer	EarthTronics Inc.
Brand	EarthTronics
Model Number	LT832850BDE
Parent	No
Classification	Standard
DLC Family Code	EMWAHX
Length	8.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	T8 Eight-Foot
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming above 10%
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	Input signal from external control source
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	210 °
Reported Light Output	4400 lm
Reported Efficacy (AC)	138 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	0
Reported IES Rf	81
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	4400 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	32 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	32 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2021-10-08	Listed	5.1	Standard
------------	--------	-----	----------

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number